

United Kingdom Overseas Territories Aviation Circular

**OTAC 39-15
121-19
125-18
135-19**

Electronic Flight Bag (EFB) Approvals

**Issue 1.00
26 January 2021**

Effective on issue

GENERAL

Overseas Territories Aviation Circulars are issued to provide advice, guidance and information on standards, practices and procedures necessary to support Overseas Territory Aviation Requirements. They are not in themselves law but may amplify a provision of the Air Navigation (Overseas Territories) Order or provide practical guidance on meeting a requirement contained in the Overseas Territories Aviation Requirements.

PURPOSE

This Overseas Territories Aviation Circular provides information regarding Electronic Flight Bags and the requirements of both the AN(OT)O and OTAR Parts 39, 121, 125 and 135 for obtaining an approval. This guidance is also intended to provide an indication of the level of knowledge and investment in resources (both human and hardware) necessary, before an operator is ready to commence the process of applying for an EFB approval.

RELATED REQUIREMENTS

This Circular relates to the use of Electronic Flight Bags (EFB) in accordance with OTAR Parts 39, 121.800, 125.800 and 135.800.

CHANGE INFORMATION

First issue.

ENQUIRIES

Enquiries regarding the content of this Circular should be addressed to Air Safety Support International at the address on the ASSI website www.airsafety.aero or to the appropriate Overseas Territory Aviation Authority.

CONTENTS

CONTENTS.....	2
ABBREVIATIONS.....	3
GLOSSARY OF TERMS.....	4
1. Introduction.....	6
2. Applicability.....	6
3. Reference Documents.....	6
4. System Description and Classification of EFB Systems.....	7
5. Hardware and Software Processes.....	10
6. Operational Assessment Processes.....	22
7. EFB Use in General Aviation Operations with Helicopters or Other Than Large or Turbojet Aeroplanes.....	33
Appendix A - Examples of Type A Software Applications.....	36
Appendix B - Examples of Type B Software Applications.....	38
Appendix C - Process for the Classification of Software Applications.....	39
Appendix D - Human Machine Interface (HMI) Assessment and Human Factors Considerations.....	41
Appendix E - Flight Crew Training.....	46
Appendix F - Software Application Documentation.....	50
Appendix G - EFB Policy and Procedures Manual.....	53
Appendix H - Airport Moving Map Display (AMMD) Application With Own-Ship Position.....	55
Appendix I - Example of Final Operational Report.....	58
Appendix J - Power Supply Considerations for Portable EFBs.....	61
Appendix K - Considerations for Rapid Depressurisation Test.....	62
Appendix L - Example of Operations Specifications and Operations Manual Content..	63

ABBREVIATIONS

AC: Advisory Circular (FAA)

ACARS: Aircraft Communications Addressing and Reporting System

AFM: Airplane Flight Manual

AFMS: Airplane Flight Manual Supplement

AMC: Acceptable Means of Compliance (EASA)

AMMD: Airport Moving Map Display

AMSL: Above Mean Sea Level

AN(OT)O: Air Navigation (Overseas Territories) Order

C-PED: Controlled Portable Electronic Device

CRM: Crew Resource Management

CS: Certification Specification (EASA)

EASA: European Aviation Safety Agency

EFB: Electronic Flight Bag

EUROCAE: European Organisation for Civil Aviation Electronics

FAA: Federal Aviation Administration

FSTD: Flight Simulation Training Devices

GNSS: Global Navigation Satellite System

GSM: Global System for Mobile Communications

HF: Human Factors

HMI: Human Machine Interface

MEL: Minimum Equipment List

MMEL: Master Minimum Equipment List

NOTOC: Notification to Captain

OS: Operating System

OTAC: Overseas Territories Aviation Circulars

OTAR: Overseas Territories Aviation Requirements

PED: Portable Electronic Device

RTCA: RTCA (formerly known as Radio Technical Commission for Aeronautics)

SATCOM: Satellite Communications

STC: Supplemental Type Certificate

TC: Type Certificate

T-PED: Transmitting Portable Electronic Device

GLOSSARY OF TERMS

Airport Moving Map Display

A software application displaying airport maps and using a navigation source to depict the aircraft current position on this map while on ground.

Consumer device

Electronic equipment primarily intended for non-aeronautical use.

Controlled Portable Electronic Device

A controlled PED is a PED subject to administrative control by the operator using it. This will include, inter alia, tracking the allocation of the devices to specific aircraft or persons and ensuring that no unauthorised changes are made to the hardware, software, or databases.

Data connectivity for EFB systems

Data connectivity for EFB system supports either uni-or bi-directional data communication between the EFB and other aircraft systems (e.g. avionics).

Direct interconnectivity between EFBs or direct connectivity between EFBs and ground systems as with T-PED (e.g. GSM, Bluetooth) are not covered by this definition.

Electronic Flight Bag

An information system for flight deck crew members which allows storing, updating, delivering, displaying, and/or computing digital data to support flight operations or duties.

EFB Administrator

An EFB administrator is a person appointed by the operator, held responsible for the administration of the EFB system within the company. The EFB administrator is the primary link between the operator and the EFB system and software suppliers.

EFB host platform

When considering an EFB system, the EFB host platform is the equipment (i.e. hardware) in which the computing capabilities and basic software (e.g. operating system, input/output software) reside.

EFB risk assessment and mitigation

A process that considers an EFB system, its software applications, and its integration inside a specific aircraft, to identify the potential malfunctions and failure scenarios, analyse their operational repercussions, and, if necessary, propose mitigation means.

EFB software application

Software installed on an EFB system that allows specific operational functionality.

EFB system

An EFB system comprises the hardware (including any battery, connectivity provision, I/O devices) and software (including databases) needed to support the intended EFB function(s).

EFB system supplier

The company responsible for developing, or for having developed, the EFB system or part of it. The EFB system supplier is not necessarily a host platform or aircraft manufacturer.

Minor failure conditions

Failure conditions which would not significantly reduce aeroplane safety, and which involve crew actions that are well within their capabilities. Minor failure conditions may include, for example, a slight reduction in safety margins or functional capabilities, a slight increase in crew workload, such as routine flight plan changes, or some physical discomfort to passengers or cabin crew. Further guidance on these failure conditions can be found in EASA AMC 25.1309.

Mounting device

A mounting device is an aircraft certified part which secures portable or installed EFB, or EFB system components.

No safety effect

Failure conditions that would have no effect on safety: for example, failure conditions that would not affect the operational capability of the aeroplane or increase crew workload. Further guidance on these failure conditions can be found in EASA AMC 25.1309.

Portable Electronic Device (PED)

PEDs are typically consumer electronic devices, which have functional capability for communications, entertainment, data processing, and/or utility. There are two basic categories of PEDs – those with and those without intentional transmitting capability; please refer to ED-130/RTCA DO-294().

Software application developer

The company responsible for developing, or for having developed a particular software application.

Transmitting PED (T-PED)

PEDs that have intended radio frequency (RF) transmission capabilities.

Viewable stowage

A device that is secured on the flight crew (e.g. kneeboard) or in/to an existing aircraft part (e.g. suction cups) with the intended function to hold charts or to hold acceptable light mass portable devices (for example an EFB of no more than 1 kg) viewable to the pilot at her/his required duty station. The device is not necessarily part of the certified aircraft configuration.

1. Introduction

This OTAC provides guidance to operators, and OTAAs, on the operational and airworthiness aspects for approving an application to use an Electronic Flight Bag.

Traditionally, some of the documentation and information available to flight crew for use on the flight crew compartment has been in paper format. Much of this information is now available in electronic format. In addition, many non-required information services, data, and company procedures may also be made available to flight or cabin crew electronically. Operators have long recognised the benefit of hosting these materials on the flight crew's EFBs.

The operator remains responsible for ensuring the accuracy of the information used and that it is derived from verifiable sources. The use of EFBs was initially intended to cover an alternative method of storing, retrieving, and using the manuals and information required to be on board by the applicable operational requirements. Subsequent technical development has led to potentially hosting on EFBs even applications using computational software (e.g. for performances), databases (e.g. digital navigation data) or real-time data coming from the avionics (e.g. Airport Moving Map Display).

The evaluation of an EFBs may have both an airworthiness and an operational aspect depending on the category/type of EFB/application used and, therefore, where necessary, to make a complete evaluation of an EFB system, there is a need for close coordination between the two processes.

The OTAC provides information on the types of EFB hardware and the associated software applications. It is a means but not the only means to apply for an EFB approval. Operators should consult with their OTAA in the interpretation of the requirements for an EFB.

2. Applicability

This OTAC is to be used by:

- (a) Commercial Air Transport operators by aeroplane or by helicopter;
- (b) applicants or holders of an aircraft TC) or STC;
- (c) applicants or holders of authorisations covering software applications hosted in EFBs; and
- (d) OTAAs who are reviewing approval applications for EFBs.

3. Reference Documents

ICAO Annex 6 Parts I, II and III

ICAO Doc 10020

EASA AMC 20-25A

FAA AC 170-76() Guidelines for the Certification, Airworthiness, and Operational Approval of Electronic Flight Bag Computing Devices

EASA CS23, CS 25, CS27, and CS 29

14 CFR Parts 23, 25, 27 and 29

4. System Description and Classification of EFB Systems

This section is divided into two parts. The first part deals with the host platform (e.g. the hardware and operating system) used to run the EFB software suite. The second part deals with the software suite which includes the EFB applications installed to provide the relevant functionality.

4.1 EFB systems hardware

This OTAC defines two possibilities for the hardware of EFB systems: portable and installed.

4.1.1 Portable EFB

Definition

A portable EFB is a portable EFB host platform, used on the flight deck, which is not part of the certified aircraft configuration.

Complementary characteristics

A portable EFB can be operated inside and outside the aircraft.

A portable EFB hosts type A and/or type B EFB software applications. In addition, it may host miscellaneous (non-EFB) software applications (see 5.2.2.3).

A portable EFB is a portable electronic device (PED), these are any kind of electronic device, typically but not limited to, consumer electronics, brought on board the aircraft by crew members, or as part of the cargo and that are not included in the approved aircraft configuration. All equipment that can consume electrical energy falls under this definition. The electrical energy can be provided from internal sources as batteries (chargeable or non-rechargeable) or the devices may also be connected to specific aircraft power sources.

The mass, dimensions, shape, and position of the portable EFB should not compromise flight safety.

A portable EFB may be provided with aircraft power through a certified power source (see 5.1.1.1.3).

If mounted, the portable EFB is easily removable from its mounting device or attached to it, without the use of tools by the flight crew, and the attachment or removal does not constitute a maintenance action.

A portable EFB may be part of a system containing EFB installed resources which are part of the certified aircraft configuration.

The installed EFB components are part of the certified aircraft configuration with the intended function to mount (see 5.1.1.1.1) the EFB to the aircraft and/or connect to other systems (see 5.1.1.1.4).

When a portable EFB is a T-PED, the conditions for use of its transmitting capability are established in the approved Aircraft Flight Manual (AFM). In absence of information in the AFM, the EFB transmitting capability may be allowed during non-critical phases of the flight (see 5.2.1.1.2).

Portable EFBs may be used in all phases of the flight if secured to a certified mount or securely attached to a viewable stowage device in a manner which allows its normal use (see 5.1.1.1.1, 5.1.1.1.2, and 5.2.1.6).

Portable EFBs not meeting the above characteristic, should be stowed during critical phases of the flight.

Portable EFBs are controlled PEDs.

Any EFB component that is either not accessible in the flight crew compartment by the flight crew members or not removable by the flight crew, should be installed as 'certificated equipment' covered by a TC, changed TC or STC.

4.1.2 **Installed EFB**

Definition

An EFB host platform installed in the aircraft and considered as an aircraft part, covered, thus, by the aircraft airworthiness approval.

Complementary characteristics

An installed EFB is managed under the aircraft type design configuration.

In addition to hosting Type A and B applications, an installed EFB may host certified applications, provided the EFB meets the certification requirements for hosting such applications, including assurance that the non-certified software applications do not adversely affect the certified application(s). For example, a robust partitioning mechanism is one possible means to ensure the independence between certified applications and the other types of applications.

4.2 **Software applications for EFB systems**

The functionality associated with the EFB system depends, in part, upon the applications loaded on the host platform. The classification of the applications, based on respective safety effects, is intended to provide clear divisions among such applications and, therefore, the assessment process applied to each.

Appendices A and B provide support regarding the classification of traditional EFB software applications. They may be used for justifying a classification provided that the application does not feature design or functional novelties introducing new ways of interaction or unusual procedures.

If an application is not listed in the appendices or presents a high degree of novelty, the classification should be established using the definitions provided hereafter and the guidance in Appendix C.

For the purpose of the following definitions, 'malfunction or misuse' means any failure, malfunction of the application, or design-related human errors that can be reasonably expected in service.

4.2.1 **Type A**

Definition

Type A applications are EFB applications whose malfunction or misuse have no safety effect.

Complementary characteristics

Type A applications:

- (a) may be hosted on either portable or installed EFBs;
- (b) do not require any approval (see paragraph 5.2.2.1); and
- (c) should follow guidance provided in Appendix D, paragraph D.2.

Examples of Type A applications can be found in Appendix A.

4.2.2 Type B

Definition

Type B applications are applications:

- (a) whose malfunction or misuse are limited to a minor failure condition; and
- (b) which do neither substitute nor duplicate any system or functionality required by airworthiness regulations, airspace requirements, or operational rules.

Complementary characteristics

Type B applications:

- (a) may be hosted on either portable or installed EFBs;
- (b) require an operational assessment as described in paragraph 5.2.2.2; and
- (c) do not require an airworthiness approval.

Examples of Type B applications can be found in Appendix B.

4.2.2.1 AMMD application with own-ship position

AMMD with own-ship position is a Type B application that is subject to the specific conditions described in Appendix H of this OTAC.

4.2.3 Miscellaneous (non-EFB) software applications

Miscellaneous software applications are non-EFB applications, supporting function(s) not directly related to operations conducted by the flight crew on the aircraft.

5. Hardware and Software Processes

The table 1 below provides a summary of the different processes presented in this chapter.

EFB Constituent		Portable EFB paragraph 4.1.1		Installed EFB paragraph 4.1.2	
		Assessment	Records or Approvals	Assessment	Records or Approvals
Hardware	EFB Installed resources mounting device	Airworthiness Design Approval process paragraph 5.1.1.1		Airworthiness Design Approval process paragraph 5.1.1.1	
	EFB host platform	Evaluation paragraph 5.2.1	As a minimum, operations Manual amended as required	Airworthiness Design Approval process paragraph 5.1.1.2	
Software	Misc software Paragraph 5.2.2.3	Operator evaluation paragraph 5.2.2.3	Ops Manual amended as required	Operator evaluation paragraph 5.2.2.3	Ops Manual amended as required
	Software Type A Paragraph 4.2.1	Operator evaluation paragraph 5.2.2.1	Ops Manual amended as required	Operator evaluation paragraph 5.2.2.1	Ops Manual amended as required
	Software Type B Paragraph 4.2.2	Evaluation Paragraph 5.2.2.2	As a minimum, ops Manual amended as required	Evaluation Paragraph 5.2.2.2	As a minimum, ops Manual amended as required

Table 1

5.1 Airworthiness approval

The airworthiness approval is necessary for installed EFB systems (see paragraph 4.1.2), as well as EFB installed resources and mounting device.

A portable EFB device does not require an airworthiness approval but its presence and use in the cockpit needs to be evaluated (see paragraph 5.2.1).

5.1.1 Hardware airworthiness approval

5.1.1.1 Installed resources

Installed resources are the input/output components external to the EFB host platform itself, such as an installed remote display, a control device (e.g. a keyboard, pointing device, switches, etc.) or a docking station.

The installed resources should be dedicated to EFB functions only, or in the case of use of resources shared with avionics, this possibility shall be part of the approved type design. It should be demonstrated, using the appropriate level of assessment, that the integration in the aircraft of the EFB and the EFB software applications does not jeopardise the compliance of the aircraft installed systems and equipment (including the shared resources) to airworthiness design certification requirements such as EASA/FAA 25.1302 or 25.1309.

Installed resources require an airworthiness design approval.

5.1.1.1.1 Mounting device

The mounting device (or other securing mechanism) attaches or allows mounting of the EFB system. The EFB system may include more than one mounting device if it consists of separate items (e.g. one docking station for the EFB host platform and one cradle for the remote display).

The mounting device should not be positioned in such a way that it obstructs visual or physical access to aircraft controls and/or displays, flight crew ingress or egress, or external vision. The design of the mounting device should allow the user easy access to any item of the EFB system, even if stowed, and notably to the EFB controls and a clear view of the EFB display while in use. The following design practices should be considered:

- (a) The mounting device and associated mechanisms should not impede the flight crew in the performance of any task (normal, abnormal, or emergency) associated with operating any aircraft system.
- (b) When the mounting device is used to secure an EFB display (e.g. portable EFB, installed EFB side display), the mount should be able to be locked in position easily. If necessary, selection of positions should be adjustable enough to accommodate a range of flight crew member preferences. In addition, the range of available movement should accommodate the expected range of users' physical abilities (i.e. anthropometrics constraints). Locking mechanisms should be of the low-wear types that will minimise slippage after extended periods of normal use.
- (c) Crashworthiness considerations should be taken into account in the design of this device. This includes the appropriate restraint of any device when in use.
- (d) When the mounting device is used to secure an EFB display (e.g. portable EFB, installed EFB side display), a provision should be provided to secure or lock the mounting device in a position out of the way of flight crew operations when not in use. When stowed, the device and its securing mechanism should not intrude into the flight crew compartment space to the extent that they cause either visual or physical obstruction of flight controls/displays and/or egress routes.
- (e) Mechanical interference issues of the mounting device, either on the side panel (side stick controller) or on the control yoke in terms of full and free movement under all operating conditions and non-interference with buckles, etc. For yoke mounted devices, (Supplemental) Type Certificate holder data should be obtained to show that the mass inertia effect on column force has no adverse effect on the aircraft handling qualities.
- (f) Adequate means should be provided (e.g. hardware or software) to shut down the portable EFB when its controls are not accessible by the pilot strapped in the normal seated position. This objective can be achieved through a dedicated installed resource certified according to 5.1.1.1 (e.g. button accessible from pilot seated position).

5.1.1.1.2 Characteristics and placement of the EFB display

(a) Placement of the display

The EFB display and any other element of the EFB system should be placed in such a way that they do not unduly impair the pilot's external view during all phases of the flight. Equally, they should not impair the view and access to any cockpit control or instrument.

The location of the display unit and the other EFB system elements should be assessed for impact on egress requirements.

When the EFB is in use (intended to be viewed or controlled), its display should be within 90 degrees on either side of each pilot's line of sight.

Glare and reflection on the EFB display should not interfere with the normal duties of the flight crew or unduly impair the legibility of the EFB data.

The EFB data should be legible under the full range of lighting conditions expected on a flight crew compartment, including use in direct sunlight.

In addition, consideration should be given to the potential for confusion that could result from presentation of relative directions when the EFB is positioned in an orientation inconsistent with that information. For example, it may be misleading if the aircraft heading is pointed to the top of the display and the display is not aligned with the aircraft longitudinal axis. This does not apply to charts that are presented in a static way (e.g. with no HMI mechanisation such like automatic repositioning), and that can be considered as similar to paper charts.

(b) Display characteristics

Consideration should be given to the long-term display degradation as a result of abrasion and ageing.

Users should be able to adjust the screen brightness of an EFB independently of the brightness of other displays on the flight crew compartment. In addition, when incorporating an automatic brightness adjustment, it should operate independently for each EFB in the flight crew compartment. Brightness adjustment using software means may be acceptable providing that this operation does not affect adversely the crew workload.

Buttons and labels should have adequate illumination for night use. 'Buttons and labels' refer to hardware controls located on the display itself.

The 90-degree viewing angle on either side of each pilot's line of sight, may be unacceptable for certain EFB applications if aspects of the display quality are degraded at large viewing angles (e.g. the display colours wash out or the displayed colour contrast is not discernible at the installation viewing angle).

(c) Applicable specifications

Each EFB system should be evaluated with regard to the requirements in this section 5.1.1.1.2.

If the display is an installed resource, it should be assessed against the applicable certification design requirement e.g. EASA/FAA 25.1302 or in accordance with the applicable aircraft type certification basis.

5.1.1.1.3 Power Sources

This section applies to design considerations for installing dedicated power port and cabling provisions for EFBs. EFB power provisions should comply with the applicable airworthiness specifications.

Connection of EFB power provisions to a non-essential, or to the least critical power bus, is recommended, so failure or malfunction of the EFB, or power supply, will not affect safe operation of aircraft critical or essential systems.

Connection to more critical aircraft power buses is, however, permitted if appropriate, taking into account the intended function of the EFB. Further considerations can be found in Appendix J of this OTAC.

In all cases, an electrical load analysis should be conducted to replicate a typical EFB system to ensure that powering or charging the EFB will not adversely affect other aircraft systems and that power requirements remain within power-load budgets.

The aircraft power source delivering power supply to the EFB system should be demonstrated to protect the aircraft electrical network from EFB system failures or malfunctions (e.g. short-circuit, over-voltages, over-load, electrical transients or harmonics, etc.). The following should be considered in the design of the power source:

- (a) A placard should be mounted beside the power outlet, containing the information needed by the flight or maintenance crews (e.g. 28 VDC, 115 VAC, 60 or 400 Hz, etc.).
- (b) The EFB power source should be designed so that it may be deactivated at any time. If the flight crew cannot quickly remove the plug, which is used to connect the EFB to the aircraft electrical network, an alternate means should be provided to quickly stop powering and charging the EFB. Circuit breakers are not to be used as switches; their use for this purpose is prohibited.
- (c) If a manual means (e.g. on/off switch) is used, this means should be clearly labelled and be readily accessible.
- (d) If an automatic means is used, the applicant should describe the intended function and the design of the automatic feature and should substantiate that the objective of deactivating the EFB power source, when required to maintain safety, is fulfilled.

Further considerations can be found in 5.1.1.1.5 which deals with connecting cables.

5.1.1.1.4 EFB data connectivity

Portable EFB having data connectivity to aircraft systems, either wired or wireless, may receive or transmit data to and from aircraft systems, provided the connection (hardware and software for data connection provisions) and adequate interface protection devices are incorporated into the aircraft type design.

A portable EFB can receive any data from aircraft systems, but data transmission from EFB is limited to:

- (a) systems whose failures have no safety effect or minor safety effect at aircraft level (e.g. printer or ACARS);
- (b) aircraft systems which have been certified with the purpose of providing connectivity to PEDs (e.g. SATCOM with a router) in accordance with the limitations established in the AFM;

- (c) systems which are completely isolated (in both directions) from the certified aircraft systems (e.g. a transmission media that receives and transmits data for Aircraft Administrative Communications purposes on the ground only); and
- (d) EFB system installed resources according to section 5.1.1.1.

EFB data connectivity should be validated and verified to ensure non-interference and isolation from certified aircraft systems during data transmission and reception.

The safety assessment of the EFB data connectivity installation should include an analysis of vulnerabilities to new threats that may be introduced by the connection of the EFB to the aircraft systems (malware and unauthorised access) and their effect on safety. This assessment is independent and does not take any credit from the operational assessment of EFB System Security (see section 6.9), which is intended to protect EFB systems themselves.

Certified aircraft systems should not be adversely affected by EFB system failures.

Any consequent airworthiness limitations should be included in the AFM (please refer to 5.1.2.1).

5.1.1.1.5 Connecting cables

If cabling is installed to mate aircraft systems with an EFB:

- (a) if the cable is not run inside the mount, the cable should not hang loosely in a way that compromises task performance and safety. Flight crew should be able to easily secure the cables out of the way during operations (e.g., cable tether straps);
- (b) cables that are external to the mounting device should be of sufficient length in order not to obstruct the use of any movable device on the flight crew compartment; and
- (c) for Part-25 airplanes, installed cables are considered electrical wiring interconnection systems and, therefore, need to comply with CS/FAR 25 subpart 1700 series electrical wiring requirements.

5.1.1.2 Installed EFB

An installed EFB is considered as part of the aircraft and, therefore, requires a full airworthiness design approval. This host platform includes the Operating System (OS).

The assessment of compliance with the airworthiness requirements would typically include two specific areas:

- (a) the safety assessment addressing failure conditions of the EFB system hardware, of any certified application (or applications ineligible as Type A and/or Type B) installed on the EFB and the partition provided for uncertified applications and miscellaneous non-EFB applications; and
- (b) hardware and operating system software qualification conducted in accordance with the necessary Development Assurance Level (DAL) for the system and its interfaces.

5.1.2 Certification documentation

5.1.2.1 Aircraft Flight Manual

For installed EFB and certified installed resources, the AFM section or an Aircraft Flight Manual Supplement (AFMS) should contain:

- (a) a statement of the limited scope of the airworthiness approval of EFBs provisions (e.g. these EFB provisions are only intended for Type A and Type B applications in accordance with this OTAC. The airworthiness approval does not replace the operational assessment for the use of the EFB system);
- (b) identification of the installed equipment which may include a very brief description of the installed system or resources; and
- (c) appropriate amendments or supplements to cover any limitations concerning:
 - (1) the use of the EFB host platform for installed EFB system; and
 - (2) the use of the installed EFB provisions/resources for portable EFB system.

For this purpose, the AFM(S) should make reference to any guidelines (relevant to the airworthiness approval), intended primarily for EFB software application developers or EFB system suppliers.

5.1.2.2 Guidelines for EFB software application developers (Installed EFB and certified installed resources)

TC/STC holders for EFB installed resources or installed EFBs should compile and maintain a guidelines document to provide a set of limitations, considerations, and guidelines to design, develop, and integrate software applications into the installed EFB or with certified resources for portable EFB. The guideline should address, at least, the following:

- (a) a description of the architecture for the EFB installed components;
- (b) the EFB component Development Assurance Level (DAL) and any assumptions, limitations, or risk mitigations means necessary to support this;
- (c) information necessary to ensure development of a software application consistent with the avionics interface and the human machine interface, that is also accurate, reliable, secure, testable, and maintainable;
- (d) integration procedures between any new software application with those already approved; and
- (e) guidelines on how to integrate any new software application into the installed platform or installed resources.

The guidelines document should be available, at least, to the aircraft operator, and to the OTAA of the operator.

5.1.2.3 Guidelines for EFB system suppliers (installed resources for portable EFBs)

TC/STC holders for installed resources of portable EFBs should provide a set of requirements and guidelines to integrate the portable EFB in the installed provisions, and to design and develop EFB software applications.

Guidelines intended primarily for use by the EFB system supplier, should address, at least, the following:

- (a) A description of the installed EFB resources and associated limitations, if any. For example:
 - (1) intended function, limitations of use, etc.;
 - (2) characteristics of the mounting devices, display units, control and pointing devices, printer, etc.;
 - (3) maximum authorised characteristics (dimensions, weight, etc.) of the portable parts of the EFB system supported by the mounting devices;
 - (4) EFB provisions architecture description, including normal/abnormal/manual/ automatic reconfigurations; and
 - (5) normal/abnormal/emergency/maintenance procedures including allowed phases of the flight.

- (b) Characteristics and limitations, including safety and security considerations concerning:
 - (1) power supply;
 - (2) laptop battery; and
 - (3) data connectivity.

The guidelines document should be available at least to the operator, and OTAA of the operator.

5.2 Operational assessment

5.2.1 Hardware operational assessment

The hardware operational assessment is focussed on the portable EFB platforms which do not require an airworthiness approval.

Paragraphs 5.2.1.1 through 5.2.1.6 need to be assessed where applicable prior to the operational use of the portable EFB.

Additionally, paragraph 5.1.1.1 contains considerations for installed resources. When any of those resources are not certified but are parts of the portable EFB, relevant criteria need to be assessed prior to the operational use.

5.2.1.1 Electromagnetic Interference (EMI) demonstrations

It is the user's/operator's responsibility to determine that the operation of a PED will not interfere in any way with the operation of aircraft equipment. which remain on (or in standby mode) during critical phases of the flight, require the additional guidance for non-interference testing contained in subparagraph 5.2.1.1.1 and if applicable 5.2.1.1.2.

If some part of the testing (for example 5.2.1.1.2(i) Test Requirement 1) has been completed during the certification of the aircraft, the corresponding TC or STC data can be used as supporting material to demonstrate safe operational use.

5.2.1.1.1 PED non-interference compliance test method

In order to operate a PED during all phases of the flight, the user/operator is responsible for ensuring that the PED will not interfere in any way with the operation of aircraft equipment.

The following methods are applicable to portable EFBs which remain 'on' (or in standby mode) during critical phases of the flight. The user/operator may use either Method 1 or Method 2 for non-interference testing.

- (a) The two following steps complete Method 1 for compliance with PED non-interference testing for all phases of the flight.
 - (1) Step 1 is to conduct an EMI test in accordance with EUROCAE Doc ED-14()/ RTCA Doc DO-160(), section 21, category M. An EFB vendor or other source can conduct this Step 1 test for an EFB user/operator. An evaluation of the results of the ED-14()/DO-160() EMI test can be used to determine if an adequate margin exists between the EMI emitted by the PED and the interference susceptibility threshold of aircraft equipment. If Step 1 testing determines that adequate margins exist for all interference (both front door and back door susceptibility), then Method 1 is complete. It is necessary to complete Step 2 testing if Step 1 testing identifies inadequate margins for interference, or either front door or back door susceptibility. (Front door emissions couple to aircraft system antennas by means of propagation through aircraft apertures such as doors and windows. Back door emissions couple to aircraft equipment, wires, and cables.)
 - (2) Step 2 testing is specific to each aircraft model in which the PED will be operated. Test the specific PED equipment in operation on the aircraft to show that no interference of aircraft equipment occurs from the operation of the PED. Step 2 testing is conducted in an actual aircraft, and credit may be given to other similarly equipped aircraft of the same make and model as the one tested.
- (b) Method 2 for compliance with PED non-interference testing for all phases of the flight is a complete test in each aircraft using standard industry practices. This should be to the extent normally considered acceptable for non-interference testing of a PED in an aircraft for all phases of the flight. Credit may be given to other aircraft of the same make and model equipped with the same avionics as the one tested.

5.2.1.1.2 Additional T-PED non-interference compliance test method

In order to activate the transmitting capability of the EFB during flight in other conditions than those certified at aircraft level (e.g. tolerance to specific T-PED models) and, hence, documented in the AFM, or equivalent document, the user/operator is responsible to ensure that the T-PED will not interfere with the operation of the aircraft equipment in any way.

Non-interference testing for T-PEDs consists of two separate test requirements:

- (a) Test Requirement 1. Each T-PED model should have an assessment of potential electro-magnetic interferences (EMI) based on a representative sample of the frequency and power output of the T-PED. This EMI assessment should be in accordance with applicable processes set forth in

EUROCAE Doc ED-130()/RTCA Doc DO-294(). The applicable DO-160() section 21 Category to be considered in the ED-130() process for an EFB used as a T-PED, is Cat M. This EMI assessment should confirm that no interference with aircraft equipment will occur as a result of intentional transmissions from these devices.

- (b) Test Requirement 2. Once an EMI assessment determines there will be no interference from the T-PED's intentional transmissions, test each T-PED model while powered but not deliberately transmitting using either Method 1 or Method 2 for basic non-interference testing requirements. This basic non-interference testing is applicable to both an EFB-integrated T-PED and a T-PED that is remote to an EFB. When an EFB has an integrated T-PED, complete the basic non-interference testing both with and without the T-PED transmit function being operative. If a T-PED is located remotely from the EFB, the T-PED basic non-interference testing is independent from the EFB non-interference testing. T-PED position is very critical to T-PED non-interference testing. Clearly define and adhere to the operating/testing locations of a T-PED in T-PED operating procedures.

Any restriction in the use of the transmitting capability should be documented in the operations manual.

5.2.1.2 Batteries

Lithium Batteries. Rechargeable lithium-type batteries are becoming more common as a source of principal power or standby/backup power in EFBs. Lithium-ion or lithium-polymer (lithium-ion polymer) batteries are two types of rechargeable lithium batteries commonly used to power EFBs. The word "battery" used in this OTAC refers to the battery pack, its cells, and its circuitry.

5.2.1.2.1 Safety Concerns

These types of batteries are vulnerable to overcharging and over-discharging, which can (through internal failure) result in overheating. Overheating may result in thermal runaway, which can cause the release of either molten lithium or a flammable electrolyte. Once one cell in a battery pack goes into thermal runaway, it produces enough heat to cause adjacent cells to go into thermal runaway. The resulting fire can flare repeatedly as each cell ruptures and releases its contents. For guidance on fighting fires caused by lithium-type batteries in PEDs, refer to FAA AC 120-80, In-Flight Fires, and Safety Alerts for Operators (SAFO) 09013, Fighting Fires Caused by Lithium Type Batteries in Portable Electronic Devices.

5.2.1.2.2 Design Recommendation

It is recommended that the rechargeable lithium-type battery design be compliant with the provisions of Institute of Electrical and Electronic Engineers (IEEE) 1625-2008, IEEE Standard for Rechargeable Batteries for Multi-Cell Mobile Computing Devices. This standard promotes design considerations for system integration, cell, pack, host device, and total system reliability. It also addresses how to maintain critical operational parameters with respect to time, environment, extremes in temperature, and the management of component failure.

5.2.1.2.3 Related Regulations

There are other regulations applicable to the use of lithium batteries onboard aircraft, including the US Department of Transportation (DOT) regulations for air travel found in Code of Federal Regulations (49 CFR) part 175, § 175.10.

DOT regulations do not allow more than 25 grams of equivalent lithium content (ELC) or 300 watt-hours per battery pack in air travel. Additional information can be found at <https://www.phmsa.dot.gov/safe-travel/batteries>. DOT regulations apply to the shipment of lithium-ion batteries, not to batteries installed in PEDs. However, if spare batteries are carried, operators should refer to the current DOT regulations.

5.2.1.2.4 Lithium Battery Safety and Testing Standards

Due to their proximity to the flight crew and potential hazard to the safe operation of the aircraft, the use of rechargeable lithium-type batteries in portable EFBs located in the aircraft flight deck call for the following standards. Operators must provide evidence of the following testing standards to determine whether rechargeable lithium-type batteries used to power EFBs are acceptable for use and for recharging. Operators must provide evidence of the standards in paragraphs (a) and either (b), (c), or (d). Refer to the following:

- (a) United Nations (UN) Transportation Regulations. UN ST/SG/AC.10/11/Rev.5, Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria.
- (b) (Underwriters Laboratory (UL). UL 1642, Standard for Lithium Batteries; UL 2054, Standard for Household and Commercial Batteries; and UL 60950-1, Information Technology Equipment - Safety.
Note: Compliance with UL 2054 indicates compliance with UL 1642.
- (c) International Electrotechnical Commission (IEC). International Standard IEC 62133, Secondary cells and batteries containing alkaline or other non-acid electrolytes – Safety requirements for portable sealed secondary cells, and for batteries made from them, for use in portable applications.
- (d) RTCA DO-311, Minimum Operational Performance Standards for Rechargeable Lithium Battery Systems. An appropriate airworthiness testing standard, such as the RTCA DO-311, can be used to address concerns regarding overcharging, over-discharging, and the flammability of cell components. RTCA DO-311 is intended to test permanently-installed equipment; however, these tests are applicable and sufficient to test EFB rechargeable lithium-type batteries. For further guidance on RTCA DO-311 testing, refer to AC 20-184, Guidance on Testing and Installation of Rechargeable Lithium Battery and Battery Systems on Aircraft.

5.2.1.2.5 Showing Compliance

The operator must possess records showing compliance to these battery standards during the authorization to use the EFB. These records may be available from the EFB manufacturer or the battery's OEM.

5.2.1.2.6 Rechargeable Lithium-Type Battery Maintenance, Storage, and Functional Check

Operators must have documented maintenance procedures for their rechargeable lithium-type batteries. These procedures must meet or exceed the OEM's recommendations. These procedures should address battery life, proper storage and handling, and safety. There should be methods to ensure the rechargeable lithium-type batteries are sufficiently charged at proper intervals and have periodic functional checks to ensure they do not experience degraded charge retention capability or other damage due to prolonged storage. These procedures should include precautions to prevent mishandling of the battery, which could cause a short circuit, damage, or other

unintentional exposure, or possibly resulting in personal injury or property damage. All replacements for rechargeable lithium batteries must be sourced from the OEM and repairs must not be made.

5.2.1.3 Power source

- (a) Portable EFB system design must consider the source of electrical power, the independence of the power sources for multiple EFBs, and the potential need for an independent battery source. A non-exhaustive list of factors to be considered includes:
 - (1) The possibility to adopt operational procedures to assure an adequate level of safety (for example minimum level of charge at pre-flight);
 - (2) The possible redundancy of portable EFBs to reduce the risk of exhausted batteries;
 - (3) The availability of back up battery packs to assure an alternative source of power.
- (b) Battery-powered EFBs that have aircraft power available for recharging the internal EFB battery (see also 5.1.1.1.3) are considered to have a suitable backup power source.
- (c) For EFBs having an internal battery power source and that are used in place of paper products required by the operating rules, the operator should either have at least one EFB connected to an aircraft power bus or established and documented mitigation means and procedures to ensure that sufficient power will be available during the whole flight with acceptable margins.
- (d) For guidance on the design and installation of aircraft electrical power sources see section 5.1.1.1.3.
- (e) If the aircraft is equipped with electrical power outlet(s) in the cockpit, the operator should ensure that their certified characteristics are compatible with the intended use for the EFB system. The powering or charging of the EFB system should be compatible with the electrical characteristics of the power supplied by the outlets in terms of power consumption, voltage, frequency, etc. in order not to impair the EFB system or other aircraft systems.

5.2.1.4 Environmental testing

Environmental testing, in particular testing for rapid depressurisation, may need to be performed when the EFB host applications that are required to be used during flight following a rapid depressurisation, and/or when the EFB environmental operational range is potentially insufficient with respect to the foreseeable cockpit operating conditions. However, since many portable EFB devices were originally consumer electronic systems accepted for aviation use, testing done on a specific EFB model configuration may be applied to other aircraft installations and these generic environmental tests may not need to be duplicated.

The operator should collect and retain:

- (a) evidence of these tests that have already been accomplished; or
- (b) suitable alternate procedures to deal with the total loss of the EFB system.

Further considerations can be found in Appendix K of this OTAC.

Testing for rapid depressurisation may need to be repeated when the EFB model identification changes, or the battery type is changed.

This testing is not equivalent to a full environmental qualification. Operators should account for the possible loss or erroneous functioning of the EFB in abnormal environmental conditions (see 6.2.2).

The safe stowage and the use of the EFB under any foreseeable cockpit environmental conditions, including turbulences, should be evaluated.

5.2.1.5 Display characteristics

Even though a portable EFB is not certified, the display characteristics should be considered during the operational assessment process. For that purpose, the material from 5.1.1.1.2 (a) and (b) apply.

For a portable EFB which is neither mounted nor stowed (e.g. handheld, or sitting on the pilot tray), the considerations on the location of the display proposed in 5.1.1.1.2 should apply at the proposed location of the display when the EFB is in use.

5.2.1.6 Viewable stowage

The viewable stowage should comply with 5.1.1.1.1.

The evaluation of the viewable stowage should be performed for a given location on the flight deck. This location should be documented and the information should be part of the EFB policy.

Some types of viewable stowage securing means may have characteristics that degrade with ageing or due to various environmental factors. In that case, the documentation should include procedures (e.g. crew procedures, checks, or maintenance actions) to ensure that the stowage characteristics remain within acceptable limits for the proposed operations. Securing means based on vacuum (e.g. suction cups) have a holding capacity that decreases with pressure. It should be demonstrated that they will still perform their intended function at operating cabin altitudes or in case of rapid depressurisation.

In addition, it should be demonstrated that if the EFB moves or is separated from its stowage, or if the viewable stowage is unsecured from the aircraft (as a result of turbulence, manoeuvring, or other action), it will not jam flight controls, damage flight deck equipment, or injure flight crew members.

5.2.2 Software operational assessment

5.2.2.1 Type A software applications

Type A software applications do not require operational approval but should follow the HMI and human factors guidance material provided in Appendix D. Type A applications hosted in portable EFBs can be used by properly trained pilots when exercising their privileges.

5.2.2.2 Type B software applications

Type B software applications do not require airworthiness approval but should be assessed through the process presented in Section 6.2. The operator responsible for the evaluation should collect and retain the documentation listed in Appendix F.

The list of Type B software application that require a documented evaluation is provided in Appendix B.

5.2.2.3 Miscellaneous (non-EFB) software applications

The use of miscellaneous software applications is out of the scope of this document but is subject to the applicable operational rules.

The EFB administrator should ensure that miscellaneous software applications do not adversely impact the operation of the EFB (refer to paragraph 7.11) and include miscellaneous software in the scope of EFB configuration management. The configuration of those applications (e.g. applications updates, installation of new applications) has to be managed by the EFB administrator.

This does not preclude EFB devices from being allocated to specific crew members.

However, and only in cases where it is demonstrated that miscellaneous software applications run in a fully segregated and partitioned way compared to EFB or avionics applications (e.g. on a separate Operating System on a distinct 'personal' hard drive partition that is selected at the boot), the administration of these miscellaneous applications can be exercised by the flight crew and not by the EFB administrator.

Examples of miscellaneous software applications are: web browser (not used for operational purposes), e-mail client, picture management application, or even applications used by ground crews (e.g. for maintenance purposes).

6. Operational Assessment Processes

The operator should ensure the continued compliance of the EFB software package with this OTAC.

When an aircraft manufacturer is seeking an operational evaluation of an EFB system or component of an EFB system prior to an operator carrying out the operational assessment, the manufacturer may file an application for an evaluation by the authority of the state of design.

The operator may demonstrate the fidelity and reliability of the system in different ways, but a detailed EFB risk assessment and suitable means of mitigation against failure or malfunction are required.

The operator may choose to keep a paper backup as a cross-check against the EFB information and as a means of mitigation against failure. A combination of solutions, with limited on-board paper backup, may also be used.

The scope of the final operational evaluation test (see paragraph 6.14) will depend on the selected solutions.

The air operations requirements do not foresee a prior approval of EFB. However, the operators' OTAA may, through their change management procedure, require the operator to notify any change concerning the EFB.

Modifications and amendments of the database and/or software may also be required by the operator's OTAA. The operator should ensure that these modifications and amendments are incorporated and that they follow the revision control procedures specified in paragraph 6.11.1.

6.1 Role of the EFB system supplier

As stated in paragraph 7, the operator should also ensure the compliance of the initial EFB software package (batch) with this OTAC at the time it is delivered.

However, an EFB system supplier may apply for an OTAA evaluation to assess conformity against this OTAC, to simplify the operator's assessment process.

6.2 Risk assessment for EFB systems

6.2.1 General

Prior to the entry into operation of any EFB system, the operator should carry out a risk assessment as part of its hazard identification and risk management process required by the OTARs.

The risk assessment should:

- (a) evaluate the risks associated with the use of an EFB and to define the appropriate mitigation;
- (b) identify potential losses of function or malfunction (detected and undetected erroneous output) and associated failure scenarios;
- (c) analyse the operational consequences of these failure scenarios;
- (d) establish mitigating measures; and
- (e) ensure that the EFB system (hardware and software) achieves at least the same level of accessibility, usability, and reliability as the means of presentation it replaces.

In considering the accessibility, usability, and reliability of the EFB system, the operator should ensure that the failure of the complete EFB system as well as individual applications, including corruption or loss of data and erroneously displayed information, has been assessed and that the risks have been mitigated to an acceptable level.

This risk assessment should be defined before the beginning of the trial period and should be amended accordingly, if necessary, at the end of this trial period. The results of the trial should establish the configuration and use of the system.

When the EFB system is intended for introduction alongside a paper-based system, only the failures that would not be mitigated by the use of the paper-based system need to be addressed. In all other cases, and especially when an accelerated introduction with a reduced trial period (as defined in 6.14) or paperless entry-into-service of a new EFB system is intended, a complete risk assessment should be carried out.

6.2.2 Assessing and mitigating the risks

Some parameters of EFB applications may depend on crew or dispatchers' entries whereas others may be parameters defaulted from within the system and subject to an administration process (e.g. the runway line-up allowance in an aircraft performance application). In the first case, mitigation would concern mainly training and crew procedures aspects whereas in the second case, mitigation means would more likely focus on administrator and data management aspects.

The analysis should be specific to the operator concerned and should address at least the following points:

- (a) Minimisation of undetected erroneous application output and assessment of the worst-case scenario;
- (b) Erroneous outputs from the software application including:
 - (1) description of corruption scenarios; and
 - (2) description of mitigation means.
- (c) Upstream processes including:
 - (1) reliability of root data used in applications (qualified/verified input data);
 - (2) software application validation and verification checks according to appropriate industry standards; and
 - (3) independence between application software, e.g. robust partitioning between Type A, B and other certified SW applications.
- (d) Description of the mitigation following detected loss of application, or detected erroneous output due to internal EFB error;
- (e) Need to access to an alternate power supply, in order to achieve an acceptable level of safety for certain software applications, especially if used as a source of required information.

As part of the mitigation, the operator should consider establishing a reliable alternative means of providing the information available on the EFB system.

The mitigation means could be, for example, one or a combination of the following:

- (a) system design (including hardware and software);
- (b) alternative EFB possibly supplied from a different power source;
- (c) EFB applications hosted on more than one platform;
- (d) paper backup (e.g. Quick Reference Handbook (QRH));
- (e) procedural means;
- (f) training; and
- (g) administration.

EFB system design features such as those assuring data integrity and the accuracy of performance calculations (e.g. a 'reasonableness' or 'range' check) may be integrated in the risk assessment performed by the operator.

When relevant, the EFB system supplier may also apply this risk assessment methodology to allow the operational environment to be taken into account and to support the development of the risk assessment by the operator.

6.3 Changes to EFB

Modifications to an EFB may have to be introduced either by the EFB system suppliers, the EFB applications developers, or by the operator itself.

Modifications which:

- (a) do not bring any change to the calculation algorithm and/or to the HMI of a type B application,

- (b) introduce a new Type A application or modify an existing one (provided its software classification remains Type A),
- (c) do not introduce any additional functionality to an existing Type B application, or
- (d) update an existing database necessary to use an existing Type B,

may be introduced by the operator without the need to notify the competent authority.

These changes should, nevertheless, be controlled and properly tested prior to use in flight.

The modifications in the following non-exhaustive list are considered to meet these criteria:

- (a) Operating system updates;
- (b) Chart or airport database update;
- (c) Update to introduce fixes (patch); and
- (d) Type A application installation and modification.

For all other types of modification, the operator should apply the change management procedure approved by in OTAA.

6.4 Dispatch considerations

The operator should establish dispatch criteria for EFB system and should ensure that the availability of the EFB system is confirmed by pre-flight checks.

Instructions to flight crew should clearly define the actions to be taken in the event of any EFB system deficiency.

Mitigation may be in the form of maintenance and/or operational procedures such as:

- (a) replacement of batteries at defined intervals as required;
- (b) fully charged backup battery on board;
- (c) procedures for the flight crew to check the battery charging level before departure; and
- (d) procedures for the flight crew to switch off the EFB in a timely manner when the aircraft power source is lost.

6.4.1 Dispatch with inoperative EFB elements

In case of partial or complete failure of the EFB, alternative dispatch procedures should be followed. These procedures should be included either in the MEL or in the Operations Manual and ensure an acceptable level of safety.

MEL coverage can be granted only when the corresponding item exists in the applicable MMEL or MMEL supplement of the aircraft type.

Particular attention should be paid to alternative dispatch procedures to obtain operational data (e.g. performance data) in case of a failure of an EFB hosting applications providing such calculated data.

When data input and output integrity is obtained by cross-checking and gross error checks, the same checking principle should apply to alternative dispatch procedures to ensure equivalent protection.

6.5 Human Factors assessment

The operator should carry out an assessment of the human machine interface, installation, and aspects governing Crew Resource Management (CRM) when using the EFB system. Elements to be assessed are provided in Appendix D.

In addition to any possible already performed authority of state of design assessment for which the operator may take credit, the human machine interface assessment should be carried by each operator for each kind of device and application installed on the EFB.

Each operator should assess the integration of the EFB into the flight deck environment, considering both physical integration (anthropometrics, physical interferences, etc.) and cognitive ergonomics (compatibility of look and feel, workflows, alerting philosophy, etc.).

6.6 Specific Considerations for mass and balance and performance applications

A specific part of the evaluation will be dedicated to the verification that aircraft performance or mass and balance data provided by the application are correct in comparison with data derived from the AFM (or other appropriate sources) under a representative cross check of conditions (e.g. for performance applications: take-off and landing performance data on a dry, wet and contaminated runway, different wind conditions and aerodrome pressure altitudes, etc.).

Further considerations regarding the assessment can be found in Appendix F.

The HMI training and crew procedures should as well be part of the evaluation.

Where there is already a certified mass and balance and performance application (e.g. hosted in the FMS), the operator should ensure independence of EFB and avionics-based algorithms or other appropriate means.

6.7 Flight crew operating procedures

6.7.1 Procedures for using EFB systems with other flight crew compartment systems

Procedures should be established to ensure that the flight crew know which aircraft system to use for a given purpose, including the EFB system. Procedures should define the actions to be taken by the flight crew when information provided by an EFB system is not consistent with that from other flight crew compartment sources, or when one EFB system shows different information than the other. If an EFB system generates information similar to that generated by existing automation, procedures should clearly identify which information source will be the primary, which source will be used for backup information, and under which conditions the backup source should be used.

6.7.2 Flight crew awareness of EFB software/database revisions

The operator should have a procedure in place to verify that the configuration of the EFB, including software application versions and, where applicable, database versions, are up to date. Flight crews should have the ability to easily verify database version effectivity on the EFB. Nevertheless, flight crews should not be required to confirm the revision dates for other databases that do not adversely affect flight operations, such

as maintenance log forms or a list of airport codes. An example of a date-sensitive revision is that applied to an aeronautical chart database. Procedures should specify what actions should be taken if the software applications or databases loaded on the EFB system are out of date.

6.7.3 Procedures to mitigate and/or control workload

Procedures should be designed to mitigate and/or control additional workload created by using an EFB system. The operator should implement procedures that, while the aircraft is in flight or moving on the ground, flight crew members do not become preoccupied with the EFB system at the same time. Workload should be allocated between flight crew members to ensure ease of use and continued monitoring of other flight crew functions and aircraft equipment. These procedures should be strictly applied in flight and should specify the times at which the flight crew may not use the EFB system.

6.7.4 Defining flight crew responsibilities for performance calculations

Procedures should be established to define any new roles that the flight crew and dispatch office may have in creating, reviewing, and using performance calculations supported by EFB systems.

6.8 Quality System

The operator should include the EFB system within their quality system and address it in their audit programme. The purpose is to provide confidence that EFB operations and administration are conducted in accordance with all applicable requirements, standards, and operational procedures.

6.9 EFB system security

The EFB system (including any means used for its updating) should be secure from unauthorised intervention (e.g. malicious software). The operator should ensure that adequate security procedures are in place to protect the system at software level and to manage hardware (e.g. identification of the person to whom the hardware is released, protected storage when the hardware is not in use). These procedures should guarantee that prior to each flight the EFB operational software works as specified and the EFB operational data is complete and accurate. Moreover, a system should be in place to ensure that the EFB does not accept a data load that contains corrupted contents. Adequate measures should be in place for compilation and secure distribution of the data to the aircraft.

The procedures should be transparent, easy to understand to follow and to oversee:

- (a) if an EFB is based on consumer electronics, e.g. a laptop, which can be easily removed, manipulated, or replaced by a similar component, then special consideration should be shown to the physical security of the hardware;
- (b) portable EFB platforms should be subject to allocation tracking to specific aircraft or persons;
- (c) where a system has input ports and especially if widely known protocols are using these ports or internet connections are offered, then special consideration should be shown to the risks associated with these ports;

- (d) where physical media is used to update the EFB system and especially if widely known types of physical media are used, then the operator should use technologies and/or procedures to assure that unauthorised content cannot enter the EFB system through these media.

The required level of EFB security depends on the criticality of the used functions (e.g. an EFB which only holds a list of fuel prices may require less security than an EFB used for performance calculations).

Beyond the level of security required to assure that the EFB can properly perform its intended functions, the level of security ultimately required depends on the abilities of the EFB.

Examples of typical safety and security defences are contained in the following non exhaustive list:

- (a) Individual system firewalls;
- (b) Clustering of systems with similar safety standards into domains;
- (c) Data encryption & authentication;
- (d) Virus scans;
- (e) Keeping the OS up to date;
- (f) Initiating air/ground connections only when required and always from the aircraft;
- (g) 'Whitelists' for allowed Internet domains;
- (h) VPNs;
- (i) Granting of access rights on a need-to-have basis;
- (j) Troubleshooting procedures should consider security threats as well as the potential root cause of EFB misbehaviour. Responses should be developed to prevent future successful attacks when relevant;
- (k) Virtualisation; and
- (l) Forensic tools and procedures.

The EFB administrator should not only keep the EFB system, but also his/her knowledge about security of EFBs systems up to date.

6.10 Electronic signatures

Regulations may require a signature to signify either acceptance or to confirm the authority (e.g. load sheet, technical logbook, NOTOC). In order to be accepted as an equivalent to a handwritten signature, electronic signatures used in EFB applications need, as a minimum, to fulfil the same objectives and should, as a minimum, assure the same degree of security as the handwritten or any other form of signature it intends to replace.

In the case of legally required signatures, an operator should have in place procedures for electronic signatures, acceptable to its OTAA, that guarantee:

- (a) **the uniqueness:** A signature should identify a specific individual and be difficult to duplicate;
- (b) **the significance:** An individual using an electronic signature should take deliberate and recognisable action to affix his or her signature;

- (c) **the scope:** The scope of information being affirmed with an electronic signature should be clear to the signatory and to subsequent readers of the record, record entry, or document;
- (d) **the signature security:** The security of an individual's handwritten signature is maintained by ensuring that it is difficult for another individual to duplicate or alter it;
- (e) **the non-repudiation:** An electronic signature should prevent a signatory from denying that he or she affixed a signature to a specific record, record entry, or document. The more difficult it is to duplicate a signature, the likelier the signature was created by the signatory; and
- (f) **the traceability:** An electronic signature should provide positive traceability to the individual who signed a record, record entry, or any other document.

An electronic signature should retain those qualities of a handwritten signature that guarantee its uniqueness. Systems using either a PIN or a password with limited validity (time-wise) may be appropriate in providing positive traceability to the individual who appended it. Advanced electronic signatures, qualified certificates and secured signature-creation devices needed to create them are typically not required for EFBs operations.

Note: The provision of secure access to EFB functions is outside the scope of this section, which only addresses the replacement of handwritten signature by an electronic one.

6.11 Role of the EFB administrator

The operator should appoint an EFB Administrator. The role of the EFB administrator is a key factor in the management of the EFB system on behalf of an operator. Complex EFB systems may require more than one individual to conduct the administration process, but one person should be designated as the EFB administrator responsible for the complete system with appropriate authority within the operator's management structure.

The EFB administrator will be the person in overall charge of the EFB system, and will be responsible for ensuring that any hardware conforms to the required specification, and that no unauthorised software is installed. He/she will also be responsible for ensuring that only the current version of the application software and data packages are installed on the EFB system.

The EFB administrator is responsible:

- (a) for all the applications installed, and for providing support to the EFB users on these applications;
- (b) for checking potential security issues associated with the application installed;
- (c) for hardware and software configuration management and for ensuring, in particular, that no unauthorised software is installed;
- (d) for ensuring that only a valid version of the application software and current data packages are installed on the EFB system; and
- (e) for ensuring the integrity of the data packages used by the applications installed.

The operator should make arrangements to ensure the continuity of the management of the EFB system in the absence of the EFB administrator.

EFB administration should be subject to independent routine audits and inspections as part of the operator's quality system (see paragraph 6.8).

Each person involved in EFB administration should receive appropriate training in their role and should have a good working knowledge of the proposed system hardware, operating system, and relevant software applications, and also of the appropriate regulatory requirements related to the use of EFB. The content of this training should be determined with the aid of the EFB system supplier or application supplier.

The administrator training material should be made available on request to the operator's OTAA.

6.11.1 The EFB Policy and Procedures Manual (EFPPM)

The (S)TC holder, the EFB system supplier or the operator in the case of consumer device should clearly identify those parts of the EFB system that can be accessed and modified by the operator's EFB administration process and those parts that are only accessible by the EFB system supplier. The EFB administrator should establish procedures, documented in an EFPPM, to ensure that no unauthorised changes take place.

The EFPPM may be fully or partly integrated in the Operations Manual and should also address the validity and currency of EFB content and databases, ensuring, thus, the integrity of EFB data. This may include establishing revision control procedures so that flight crews and others can ensure that the contents of the system are current and complete. These revision control procedures may be similar to the revision control procedures used for paper or other storage means.

For data that is subject to a revision cycle control process, it should be readily evident to the user which revision cycle has been incorporated in the information obtained from the system. Procedures should specify what action to take if the applications or databases loaded on the EFB are out of date. This manual may include, but is not limited to, the following:

- (a) Document changes to content/databases;
- (b) Notification to crews of updates;
- (c) If any applications use information that is specific to the aircraft type or tail number, ensuring that the correct information is installed on each aircraft;
- (d) Procedures to avoid corruption/errors during changes to the EFB system; and
- (e) In case of multiple EFBs in the flight crew compartment, procedures to ensure that they all have the same content/databases installed.

The EFB administrator should be responsible for the procedures and systems, documented in the EFPPM that maintain EFB security and integrity. This includes system security, content security, access security, and protection against harmful software (see paragraph 6.9).

Note: An example of the subjects relevant for inclusion in the EFPPM is included at Appendix G.

6.12 EFB system maintenance

Procedures should be established for the routine maintenance of the EFB system and how unserviceability and failures are to be dealt with to ensure that the integrity of the EFB system is assured. Maintenance procedures may also need to include the secure handling of updated information and how it is accepted and then promulgated in a timely and complete format to all users and aircraft platforms.

The operator is responsible for the maintenance of EFB system batteries, and should ensure that they are periodically checked and replaced as required. This task should be included in the Maintenance Programme.

Should a fault or failure of the system arise, it is essential that such failures are brought to the immediate attention of the flight crew and that the system is isolated until rectification action is taken. In addition to backup procedures, to deal with system failures, a reporting system will need to be in place so that the necessary action, either to a particular EFB system, or to the whole system, is taken in order to prevent the use of erroneous information by flight crews.

6.13 Flight crew training

Flight crew should be given specific training on the use of the EFB system before it is operationally used.

Training should include the following:

- (a) An overview of the system architecture;
- (b) Pre-flight checks of the system;
- (c) Limitations of the system;
- (d) Specific training on the use of each application and the conditions under which the EFB may and may not be used;
- (e) Restrictions on the use of the system, including where some or the entire system is not available;
- (f) Procedures for normal operations, including cross-checking of data entry and computed information;
- (g) Procedures to handle abnormal situations, such as a late runway change or diversion to an alternate aerodrome;
- (h) Procedures to handle emergency situations;
- (i) Phases of the flight when the EFB system may and may not be used;
- (j) CRM and human factor considerations on the use of the EFB; and
- (k) Additional training for new applications or changes to the hardware configuration.

As far as is practicable, it is recommended that the training simulators' environments (FSTDs) include the EFBs in order to offer a higher level of representativeness.

Consideration should also be shown to the role that the EFB system plays in operator proficiency checks as part of recurrent training and checking, and to the suitability of the training devices used during training and checking.

EFB training should be included in the relevant training programme and approved by the operator's OTAA.

Note: Further guidance is provided in Appendix E.

6.14 Operational evaluation test

The operator should conduct an operational evaluation test which should allow verifying that the above elements have been satisfied before final decision on the operational use of the EFB.

The operator should notify its competent authority of its intention to conduct an operational evaluation test by sending a plan which should contain at least the following information:

- (a) starting date of the operational evaluation test;
- (b) duration;
- (c) aircraft involved;
- (d) EFB hardware and type(s) of software(s); and
- (e) when no paper backup is retained:
 - (1) EFB detailed risk assessment,
 - (2) simulator LOFT session programme, and
 - (3) proposed flights for the competent authority observation flights.

6.14.1 Applications replacing paper products with an initial retention of paper backup

Where paper is initially retained as backup, the operational evaluation test should consist of an in-service proving period no longer than six months. A reduction to no less than three months may be considered taking into account the following criteria:

- (a) the operator's previous experience with EFBs,
- (b) the intended use of the EFB system, and
- (c) the mitigation means defined by the operator.

An operator wishing to reduce the six months operational evaluation test should submit to its competent authority a request with justification in its operational evaluation plan.

The operator's OTAA may ask for an operational evaluation test lasting more than six months if the number of flights operated in this period is not considered sufficient to evaluate the EFB system.

The purpose of the in-service proving period is for the operator to demonstrate that the EFB system provides an acceptable level of accessibility; usability and reliability to those required by the applicable operational requirements. In particular that:

- (a) the flight crews are able to operate the EFB applications without reference to paper;
- (b) the operator's administration procedures are in place and function correctly;
- (c) the operator is capable of providing timely updates to the applications on the EFB, where a database is involved;
- (d) the introduction of the EFB without paper backup does not adversely affect the operator's operating procedures and alternative procedures for use when the EFB system is not available provide an acceptable equivalent;

- (e) for a system including uncertified elements (hardware or software), that the system operates correctly and reliably; and
- (f) the EFB risk assessment, as required under 6.2, is adequate to the type of operations intended after the operational evaluation test (with or without paper backup).

The results of the demonstration may be documented in the form of a report from the in-service proving period on the performance of the EFB system. The operator may remove the paper backup once it has shown that the EFB system is sufficiently robust.

6.14.2 Applications replacing paper products without paper backup at commencement of operations and other applications

Where an operator seeks to start operations without paper backup, the operational evaluation test should consist of the following elements:

- (a) a detailed review of the EFB risk assessment;
- (b) a simulator LOFT session to verify the use of the EFB under operational conditions including normal, abnormal, and emergency conditions; and
- (c) observation by the competent authority of the initial operator's line flights.

The operator should demonstrate that they will be able to continue to maintain the EFB to the required standard through the actions of the Administrator and Compliance Monitoring Programme.

6.15 Final operational report

The operator should produce and retain a final operational report, which summarises all activities conducted and the means of compliance used, supporting the operational use of the EFB system. An example of typical items that the operator should include in this report is provided in Appendix I.

6.16 Issuance of EFB Operations Specifications and Approval

The OTAA granting a specific EFB approval to the operator should update the operations specifications with an EFB entry.

The operations specifications will reference the location in the operations manual where more details of the approved EFB applications can be found (see Appendix L).

7. EFB Use in General Aviation Operations with Helicopters or Other Than Large or Turbojet Aeroplanes

7.1 General

7.1.1 Operators involved in general aviation with helicopters or other than large or turbojet aeroplanes, should consider the following provisions of this section 7 before using an EFB.

7.1.2 The operator should also follow the provisions of 4.1.1 of this OTAC when using a portable EFB.

7.2 Pilot Operating Procedures

To ensure that adequate guidance is available for use of the EFB applications, the user guide established by the software developer should be available to the pilot.

7.3 Pilot Training

The pilot should be familiar with EFB use before using it in-flight. Changes to EFB hardware or software may warrant additional familiarization.

7.4 EFB Risk Assessment

For general aviation operations, hazard assessment in the traditional sense is not practical; therefore, the following mitigations are presented to address risks associated with EFB use. Before each flight, the pilot should conduct the following checks to ensure the continued safe operation of the EFB during the flight:

- (a) general check of the EFB operation by switching it ON and checking that the applications intended to be used in-flight are operative;
- (b) check battery or other power sources to ensure the availability of the EFB during taxi and flight operations, including diversions and reasonable delays;
- (c) check for currency of EFB databases (effective dates), (e.g. aeronautical charts, performance calculation, and weight and balance applications); and
- (d) check that an appropriate backup is available when using an application displaying information or data required to be on board.

7.5 EFB Functions

7.5.1 If EFB applications provide functions that display information related to the aircraft position in-flight, navigation, terrain or traffic surroundings or altitude, the pilot should be aware of the potential misleading or erroneous information displayed and should only use these functions as an advisory means.

7.5.2 When using an aeronautical chart, performance calculation, mass and balance or in-flight weather application, or an airport moving map display (AMMD), the following considerations should be taken into account by the pilot:

- (a) *Aeronautical chart application.* The aeronautical charts that are depicted should contain the information necessary, in appropriate form, to conduct the flight safely. Consideration should be given to the size and resolution of the display to ensure legibility.
- (b) *Performance calculation and mass and balance (M&B) application.* Prior to the first use of a performance or M&B application and following any update of the database supporting the application, the operator should obtain assurance that the output of the application corresponds with the data derived from the AFM (or other appropriate sources).
- (c) *Airport moving map display application.* An AMMD application should not be used as a primary means of navigation for taxi; outside references remain primary.
- (d) *In-flight weather application.* The displayed meteorological information may be forecast, observed, or both and may be updated on the ground or in-flight. It should be based on data from providers approved by the meteorological authority concerned or other sources approved by the operator.

Consideration should be given to the latency of meteorological information and the hazards associated with utilization of latent information. Pilots should only use in-flight weather applications for broad strategic avoidance of adverse meteorological conditions.

7.6 Evaluation Process

For these types of operations, an evaluation process is not required but it is nevertheless recommended that pilots and/or the operator/owner undergo an evaluation period to ensure that mitigations to risk, including EFB failures, EFB misuse and other EFB malfunctions, are addressed. During this period, the pilot or owner/operator should validate that the EFB is as available and reliable as the paper-based system being replaced, if applicable.

Appendix A - Examples of Type A Software Applications

Type A applications are EFB applications whose malfunction or misuse would have no adverse effect on the safety of any flight operation, i.e. a hazard level defined as no greater than a 'no safety effect' failure condition classification.

Such applications might typically be, but not limited to:

- (a) browser displaying:
 - (1) the certificates and other documents required to be carried by the applicable operational regulations and where copies are acceptable such as:
 - (i) the certificate of airworthiness (CofA);
 - (ii) the certificate of registration (CofR);
 - (iii) the noise certificate, and its English translation if applicable;
 - (iv) the air operator certificate (AOC);
 - (v) the operations specifications relevant to the aircraft type, issued with the AOC;
 - (vi) certified copies of documents related to any Article 83bis agreements;
 - (vii) the Third-Party Liability Insurance Certificate(s); and
 - (viii) the aircraft continuing airworthiness records, including the technical log (flight crew view thereof);
 - (2) some manuals and additional information and forms required to be carried by the applicable operational regulations such as:
 - (i) notification of special categories of passenger (SCPs) and special loads; and
 - (ii) passenger and cargo manifests, if applicable; and
 - (3) other information within the operator's aircraft library such as:
 - (i) airport diversion policy guidance, including a list of special designated airports and/or approved airports with emergency medical service (EMS) support facilities;
 - (ii) maintenance manuals;
 - (iii) Emergency response guidance for aircraft incidents involving dangerous goods (ICAO Doc 9481-AN/928);
 - (iv) aircraft parts manuals;
 - (v) service bulletins/published Airworthiness Directives, etc.;
 - (vi) current fuel prices at various airports;
 - (vii) trip scheduling and bid lists;
 - (viii) passenger information requests;
 - (ix) check airman and flight instructor records; and
 - (x) Flight crew currency requirements.

- (b) interactive applications for crew rest calculation in the framework of flight time limitations;
- (c) interactive forms to comply with the reporting requirements of the operator's OTAA and the operator;
- (d) applications that make use of aircraft administrative communications (AAC) to collect, process and then disseminate data that has no effect on the safe operation of an aircraft.

Appendix B - Examples of Type B Software Applications

A non-exhaustive list of possible Type B software applications, that are to be evaluated, is provided in this Appendix.

- (a) Document Browser displaying the following documents, interactive or not, or not in pre-composed format, and not driven by sensed aircraft parameters:
 - (1) The manuals and additional information and forms required to be carried by Regulations such as:
 - (i) The Operations Manual (including the MEL and CDL);
 - (ii) The Aircraft Flight Manual;
 - (iii) The Operational Flight Plan;
 - (iv) Meteorological information including with graphical interpretation;
 - (v) ATS Flight Plan;
 - (vi) Notices to Airmen (NOTAMs) and Aeronautical Information Service (AIS) briefing documentation;
 - (2) Electronic aeronautical chart applications including en route, area, approach, and airport surface maps; these applications may offer features such as panning, zooming, scrolling, and rotation, centring and page turning, but without display of aircraft/own-ship position;
 - (3) Use of Airport Moving Map Displays (AMMD) applications;
 - (4) Applications that make use of the internet and/or other aircraft operational communications (AOC) or company maintenance-specific data links to collect, process, and then disseminate data for uses such as spare parts and budget management, spares/inventory control, unscheduled maintenance scheduling, etc;
 - (5) Cabin-mounted video and aircraft exterior surveillance camera displays;
 - (6) Aircraft performance calculation application that uses algorithmic data or calculates using software algorithms to provide:
 - (i) take-off, en route, approach and landing, missed approach, etc. performance calculations providing limiting masses, distances, times and/or speeds;
 - (ii) power settings, including reduced take-off thrust settings;
 - (iii) mass and balance calculation application used to establish the mass and centre of gravity of the aircraft and to determine that the load and its distribution is such that the mass and balance limits of the aircraft are not exceeded;
 - (7) Applications providing in-flight weather information.

Appendix C - Process for the Classification of Software Applications

1. Purpose

As described in 4.2, the classification of the Type A and Type B EFB applications is based on the severity of failure conditions resulting from malfunctions and misuse (hereinafter referred to as 'failures') of the EFB applications.

It is not required to perform a full system safety assessment (as defined in EASA/FAA 25.1309) in order to classify EFB applications.

In practice, the assessment of these failure conditions can be achieved through the application at software level of the process described in chapter 2 of this Appendix.

The severity of the failure conditions will determine the classification of the EFB applications.

2. Process

As a first step, it should be verified that the application does not belong to the following list of applications that are not eligible for classification as either type A or B:

Applications:

- (a) displaying information which may be tactically used by the flight-crew members to check, control, or deduce the aircraft position or trajectory, either to follow the intended navigation route or to avoid adverse weather, obstacles or other traffic, in flight or on ground;
- (b) displaying information which may be directly used by the flight crew to assess the real-time status of aircraft critical and essential systems, as a replacement for existing installed avionics, and/or to manage aircraft critical and essential systems following failure;
- (c) communications with air traffic services;
- (d) sending data to the certified aircraft systems other than the EFB installed/shared resources.

Then, this process should:

- (a) identify failure conditions resulting from potential losses of function or malfunction (detected and undetected erroneous output) with consideration of any relevant factors (aircraft/system failures, flight crew procedures, operational or environmental conditions, etc.) which would alleviate or intensify the effects; and
- (b) classify the failure conditions according to the severity of their effects (using EASA/FAA 25.1309 definitions).

Failure conditions classified as minor should then be verified through a qualitative appraisal of the integrity and safety of the system design and installation. Software involved in Minor Failure Condition should be classified as level D according to the relevant industry standard (e.g. those referenced in EASA AMC/AC 20-115()).

Software applications with failure conditions classified above minor are ineligible as EFB Type A or B applications.

Notes:

- The severity of the failure conditions linked to displaying a function already existing in the certified type design, or already authorised through an ETSO, and used with same concept of operation, cannot be less than already assessed for this function;
- The data resulting from this process may be reused by the operators in the context of the EFB risk assessment process described in chapter 6.2.2.

Appendix D - Human Machine Interface (HMI) Assessment and Human Factors Considerations

1 General principles

This Appendix provides Guidance Material for the assessment of the human machine interface associated with the EFB system. It provides general criteria that may be applied during assessments conducted during both the airworthiness approval and operational assessment and is restricted to human factors assessment techniques and means of compliance. The process for division of responsibilities and who does what is contained within the main body of the OTAC.

Note: Where an assessment is conducted as part of an airworthiness design approval e.g. for an installed EFB system or installed resources for a portable EFB, EASA/FAA 25.1302 titled 'Installed systems and equipment for use by the flight crew' or applicable airworthiness basis should be applied.

2 Common considerations

2.1 Human machine interface

The EFB system should provide a consistent and intuitive user interface, within and across the various hosted applications. This should include, but not be limited to, data entry methods, colour-coding philosophies, and symbology.

2.2 Legibility of text

Text displayed on the EFB should be legible to the typical user at the intended viewing distance(s) and under the full range of lighting conditions expected on a flight crew compartment, including use in direct sunlight. Users should be able to adjust the screen brightness of an EFB independently of the brightness of other displays on the flight crew compartment. In addition, when automatic brightness adjustment is incorporated, it should operate independently for each EFB in the flight crew compartment. Buttons and labels should be adequately illuminated for night use. All controls should be properly labelled for their intended function. Consideration should be given to the long-term display degradation as a result of abrasion and ageing.

2.3 Input devices

In choosing and designing input devices such as keyboards or cursor control devices, applicants should consider the type of entry to be made and flight crew compartment environmental factors, such as turbulence, that could affect the usability of that input device. Typically, the performance parameters of cursor control devices should be tailored for the intended application function as well as for the flight crew compartment environment.

2.4 General EFB design guidelines

2.4.1 Consistency

2.4.1.1 Consistency between EFBs and applications

Particular attention should be paid to the consistency of all interfaces, in particular when a provider develops the software application and a different organisation integrates it into the EFB.

2.4.1.2 Consistency with flight deck applications

Whenever possible and without compromising innovation in design/use, EFB user interfaces should be consistent with the other flight deck avionics applications with regard to design philosophy, look and feel, interaction logics and workflows.

2.4.2 Messages and the use of colours

For any EFB system, EFB messages and reminders should meet the requirements in EASA/FAA 23.1322, 25.1322 or applicable certification basis, as is appropriate for the intended aircraft. While the regulations refer to lights, the intent should be generalised to extend to the use of colours on displays and controls.

That is, colour 'red' is to be used only to indicate a warning level condition.

'Amber' is to be used to indicate a caution level condition.

Red and amber colours should be limited and considerate. Any other colour may be used for items other than warnings or cautions, providing that the colours used, differ sufficiently from the colours prescribed to avoid possible confusion. EFB messages and reminders should be integrated with (or compatible with) presentation of other flight crew compartment system alerts. EFB messages, both visual and auditory, should be inhibited during critical phases of the flight.

Flashing text or symbols should be avoided in any EFB application. Messages should be prioritised, and the message prioritisation scheme evaluated and documented.

Additionally, during critical phases of the flight, required flight information should be continuously presented without un-commanded overlays, pop-ups, or pre-emptive messages, excepting those indicating the failure or degradation of the current EFB application. However, if there is a regulatory or Technical Standard Order (TSO) requirement that is in conflict with the recommendation above, those should have precedence.

2.4.3 System error messages

If an application is fully or partially disabled, or is not visible or accessible to the user, it may be desirable to have a positive indication of its status available to the user upon request. Certain non-essential applications such as e-mail connectivity and administrative reports may require an error message when the user actually attempts to access the function rather than an immediate status annunciation when a failure occurs. EFB status and fault messages should be prioritised and the message prioritisation scheme evaluated and documented.

2.4.4 Data entry screening and error messages

If user-entered data is not of the correct format or type needed by the application, the EFB should not accept the data. An error message should be provided that communicates which entry is suspect and specifies what type of data is expected. The EFB system should incorporate input error checking that detects input errors at the earliest possible point during entry, rather than on completion of a possibly lengthy invalid entry.

2.5 Error and failure modes

2.5.1 Flight crew error

The system should be designed to minimise the occurrence and effects of flight crew error and maximise the identification and resolution of errors. For example, terms for specific types of data or the format in which latitude/longitude is entered should be the same across systems. Data entry methods, colour-coding philosophies, and symbology should be as consistent as possible across the various hosted EFB applications. These applications should also be compatible with other flight crew compartment systems.

2.5.2 Identifying failure modes

The EFB system should be capable of alerting the flight crew of probable EFB system failures.

2.6 Responsiveness of application

The system should provide feedback to the user when user input is accepted. If the system is busy with internal tasks that preclude immediate processing of user input (e.g. calculations, self-test, or data refresh), the EFB should display a 'system busy' indicator (e.g. clock icon) to inform the user that the system is occupied and cannot process inputs immediately.

The timeliness of system response to user input should be consistent with an application's intended function. The feedback and system response times should be predictable to avoid flight crew distractions and/or uncertainty.

2.7 Off-screen text and content

If the document segment is not visible in its entirety in the available display area, such as during 'zoom' or 'pan' operations, the existence of off-screen content should be clearly indicated in a consistent way. For some intended functions it may be unacceptable if certain portions of documents are not visible. This should be evaluated based on the application and intended operational function. If there is a cursor, it should be visible on the screen at all times while in use.

2.8 Active regions

Active regions are regions to which special user commands apply. The active region can be text, a graphic image, a window, frame, or other document object. These regions should be clearly indicated.

2.9 Managing multiple open applications and documents

If the electronic document application supports multiple open documents, or the system allows multiple open applications, indication of which application and/or document is active should be continuously provided. The active document is the one that is currently displayed and responds to user actions. Under non-emergency, normal operations, the user should be able to select which of the open applications or documents is currently active. In addition, the user should be able to find which flight crew compartment applications are running and switch to any one of these applications easily. When the user returns to an application that was running in the background, it should appear in the same state as when the user left that application, with the exception of differences stemming from the progress or completion of processing performed in the background.

2.10 Flight crew workload

The positioning and procedures associated with the use of the EFB should not result in unacceptable flight crew workload. Complex, multi-step data entry tasks should be avoided during take-off, landing, and other critical phases of the flight. An evaluation of the EFB intended functions should include a qualitative assessment of incremental pilot workload, as well as pilot system interfaces and their safety implications.

3 Specific application considerations

3.1 Approach/departure and navigation chart display

The approach, departure, and navigation charts that are depicted should contain the information necessary, in appropriate form, to conduct the operation to at least a level of safety equivalent to that provided by paper charts. It is desirable that the EFB display size is at least as large as current paper approach charts and that the format be consistent with current paper charts.

The HMI assessment is key to identifying acceptable mitigation means, e.g.:

- (a) to establish procedures to reduce the risk of making errors;
- (b) to control and mitigate additional workload related to EFB use;
- (c) to ensure consistency of colour coding and symbology philosophies, between EFB applications and their compatibility with other flight crew compartment applications; and
- (d) to consider aspects of Crew Resource Management (CRM) when using an EFB system.

3.2 Performance applications and mass & balance calculations

Input data and output data (results) shall be clearly separated from each other. All the information necessary for a given calculation task should be presented together or easily accessible.

All data required for the performance and mass & balance applications should be asked for or displayed, including correct and unambiguous terms (names), units of measurement (e.g. kg or lbs), and when applicable index system and CG-position declaration (e.g. Arm/%MAC). The units should match the ones from the other cockpit sources for the same kind of data.

Airspeeds should be provided in a way directly useable in the cockpit unless the unit clearly indicates otherwise (e.g. KCAS). Any difference in the type of airspeed provided by the EFB application and the type provided by the AFM or FCOM performance charts should be mentioned in the pilot guides and training material. If the application allows to compute both dispatch (regulatory, factored) and other results (e.g. in-flight or unfactored), the flight crew should be made aware of the active mode.

Inputs

The application should allow to clearly distinguish user entries from default values or entries imported from other aircraft systems.

Performance applications should offer to the flight crew the ability to check whether a certain obstacle is included in the performance calculation and/or to include revised or new obstacle information in the performance calculation.

Outputs

All critical performance calculation assumptions (e.g. use of thrust reversers, full or reduced thrust/power rating) should be clearly displayed. The assumptions made about any calculation should be at least as clear to pilots as similar information would be on a tabular chart.

All output data should be available in numbers.

The application should indicate if a set of entries results in an unachievable operation (for instance a negative stopping margin) with a specific message or colour scheme. This should be done in accordance with D.2.4.2 (Messages and the use of colours).

In order to allow a smooth workflow and to prevent data entry errors, the layout of the calculation outputs should be such that it is not inconsistent with the data entry interface of the aircraft applications in which the calculation outputs are used (e.g. Flight Management Systems).

Modifications

The user should be able to modify performance calculations easily, especially when making last minute changes.

Calculation results and any outdated input fields should be deleted:

- (a) when modifications are entered;
- (b) when the EFB is shut down or the performance application is closed; and
- (c) when the EFB or the performance application have been in a standby or 'background' mode long enough, i.e. such that it is likely that when it is used again the inputs or outputs are outdated.

Appendix E - Flight Crew Training

The purpose of this Appendix is to describe considerations for training and checking when Standard Operating Procedures (SOP) are dependent on the use of an EFB system.

1 EFB training and checking

1.1 Assumptions regarding flight crew previous experience

Training for the use of the EFB should be for the purpose of operating the EFB itself and the applications hosted on it, and should not be intended to provide basic competence in areas such as aircraft performance, etc. Initial EFB training, therefore, should assume basic competence in the functions addressed by the software applications installed.

Training should be adapted to the crew experience and knowledge.

1.2 Programmes crediting previous EFB experience

Training programmes for the EFB may take credit for previous EFB experience. For example, previous experience of an aircraft performance application hosted on a portable EFB and using similar software may be credited toward training on an installed EFB with a performance application.

1.3 Initial EFB training

Training required for the grant of an aircraft type rating may not recognise variants within the type nor the installation of particular equipment. Any training for the grant of a type qualification need not, therefore, recognise the installation or use of an EFB unless it is installed equipment across all variants of the type. However, where training for the issue of the type rating is combined with the operator's conversion course, the training syllabus should recognise the installation of the EFB where the operator's SOPs are dependent on its use.

Initial EFB Training may consist of both ground-based and in-flight training depending on the nature and complexity of the EFB system. An operator or approved training organisation (ATO) may use many methods for ground-based EFB training including written hand-outs or FCOM material, classroom instruction, pictures, videotape, ground training devices, computer-based instruction, FSTD, and static aircraft training. Ground-based training for a sophisticated EFB lends itself particularly to CBT-based instruction. In-flight EFB training should be conducted by a suitably qualified person during Line Flying Under Supervision (LIFUS) or during Differences, Conversion or Familiarisation Training.

1.3.1 Areas of emphasis during initial EFB training

- (a) The use of the EFB hardware and the need for proper adjustment of lighting, etc. when the system is used in-flight;
- (b) The intended use of each software application together with limitations and prohibitions on their use;
- (c) If an aircraft performance application is installed, proper cross-checking of data input and output;
- (d) If a terminal chart application is installed, proper verification of the applicability of the information being used;

- (e) If a moving map display is installed, the need to avoid fixation on the map display; and
- (f) Failure of component(s) of the EFB.

1.3.2 Typical initial EFB training

The following might be a typical training syllabus, if not contrasting with the operational suitability data provided by the aircraft manufacturer.

1.3.2.1 Ground-based training

- (a) System architecture overview;
- (b) Display Unit features and use;
- (c) Limitations of the system;
- (d) Restrictions on the use of the system;
 - (1) Phases of the flight;
 - (2) Alternate procedures (e.g. MEL).
- (e) Applications as installed;
- (f) Use of each application;
- (g) Restrictions on the use of each application;
 - (1) Phases of the flight;
 - (2) Alternate procedures (e.g. MEL).
- (h) Data input;
- (i) Cross-checking data input and output; and
- (j) Use of data output.

1.3.2.2 Flight training

- (a) Practical use of the Display Unit;
- (b) Display Unit Controls;
- (c) Data input devices;
- (d) Selection of applications;
- (e) Practical use of applications;
- (f) CRM and human factor considerations;
- (g) Situational awareness;
- (h) Avoidance of fixation;
- (i) Cross-checking data input and output; and
- (j) Practical integration of EFB procedures into SOPs.

1.4 Initial EFB checking

1.4.1 Initial ground EFB checking

The check conducted following the ground-based element of Initial EFB Training may be accomplished by questionnaire (oral or written) or as an automated component of EFB computer-based training depending on the nature of the training conducted.

1.4.2 Skill test & proficiency check

Where the operator's SOPs are dependent on the use of the EFB on the particular type or variant, proficiency in the use of the EFB should be assessed in the appropriate areas.

1.4.3 Operator proficiency check

The flight crew should demonstrate their competence in carrying out normal procedures during the Operator Proficiency Check (OPC). Therefore, where an operator's SOPs are dependent on the use of an EFB, proficiency in its use should be assessed during the OPC. Where the OPC is performed on an FSTD not equipped with the operator's EFB, proficiency should be assessed by another acceptable means.

1.4.4 Line check

The flight crew should demonstrate their competence in carrying out normal procedures during the line check. Therefore, where an operator's SOPs are dependent on the use of an EFB, proficiency in its use should be assessed during line check.

1.4.5 Areas of emphasis during EFB checking

- (a) Proficiency in the use of each EFB application installed;
- (b) Proper selection and use of EFB displays;
- (c) Where an aircraft performance application is installed, proper cross-checking of data input and output;
- (d) Where a terminal chart application is installed, proper check of the validity of the information and the use of the chart clip function;
- (e) Where a moving map display is installed, maintenance of a proper outside visual scan without prolonged fixation on EFB operation, especially during the taxiing operations; and
- (f) Actions following the failure of component(s) of the EFB, including hot EFB battery.

2 Differences or familiarisation training

When the introduction of the use of an EFB requires Differences or Familiarisation Training to be carried out the elements of Initial EFB Training should be used, as described above.

3 Recurrent EFB training and checking

3.1 Recurrent EFB training

Recurrent training is normally not required for the use of an EFB, provided the functions are used regularly in line operations. Operators should be encouraged, however, to include normal EFB operations as a component of the annual ground and refresher training.

In the case of mixed fleet flying, or where the EFB is not installed across the fleet, additional recurrent training should be applied. Initial training programme developed under E.1.3 is considered to be sufficient.

3.2 Recurrent EFB Checking

Recurrent EFB checking should consist of those elements of the licence proficiency check, the operator proficiency check and the line check applicable to the use of an EFB as described in paragraphs E.1.4.2, E.1.4.3, and E.1.4.4. Areas of emphasis are as described in paragraph E.1.4.5.

4 Suitability of training devices

Where the operator's SOPs are dependent on the use of an EFB, it is recommended that the EFB is present during the operator's training and checking. Where present, the EFB should be configured and operable in all respects as per the relevant aircraft. This should apply to:

- (a) the operator's conversion course;
- (b) Differences or familiarisation training; and
- (c) Recurrent training and checking.

Where the EFB system is based on a portable device used without any installed resources, it is recommended that the device is present and operable and used during all phases of the flight during which it would be used under the operator's SOPs.

For all other types of EFB system, it is recommended that the device is installed and operable in the training device (FFS) and used during all phases of the flight during which it would be used under the operator's SOPs. However, an operator may define an alternative means of compliance when the operator's EFB system is neither installed nor operable in the training device.

Note: It is not necessary for the EFB to be available for that training and checking which is not related to the operator and the operator's SOPs.

Where the EFB is installed equipment in the basic aircraft type or variant, the installation and use of the EFB in the training device is required for the training and checking for the issue of the type rating and for the checking for the renewal or revalidation of the type rating.

Appendix F - Software Application Documentation

The operator should retain the following documentation:

- (a) Functional description document (for the initial assessment and any subsequent functional change);
- (b) Release notes (for both initial and all subsequent software releases) or equivalent;
- (c) Version description document (for both initial and all subsequent releases);
- (d) First article inspection report (refers to quality controlled release of the EFB Software Application);
- (e) Ground viewer (to enable user validation of the software releases and data base releases and updates);
 - (1) Viewers should use the same software components as the airborne application; and
 - (2) Viewers should enable user validity checking of airborne data bases before installation on an aircraft.

1 Additional requirements for performance applications for take-off, landing and mass & balance calculations

1.1 General

The performance and mass & balance applications should be based on existing published data found in the AFM or performance manual and deliver results that allow the crew to operate in compliance with the appropriate OPS regulations. The applications may use algorithms or data spread sheets to determine results. They may have the ability to interpolate within but should not extrapolate beyond the information contained in the published data for the aircraft.

If the program is designed to be used by operators under different regulation frameworks and allows to choose between the OTAAs and other reference regulations, this choice should be protected so that it is accessible only to the administrator.

To protect against intentional and unintentional modifications, the database files related to performance and mass & balance (performance database, airport database, etc.) integrity should be checked by the program before performing calculation. This check can be run once at the start-up of the application.

Each software version should be identified by a unique version number. Only specific modules of the performance or M&B software application are approved, for a specific software revision and on a specific host (e.g. computer model). The performance and mass & balance applications should keep a trace of each computation performed (inputs and outputs) and the airline should have procedures in place to retain this information.

1.2 Testing

The demonstration of the compliance of a performance or mass & balance application should include evidence of the software testing activities performed with the software version candidate for operational use.

The testing can be performed either by the operator or a third party, as long as the testing process is documented, and the responsibilities identified.

The testing activities should include HMI testing, reliability testing, and accuracy testing.

HMI testing should demonstrate that the application is not error-prone and that calculation errors can be detected by the crew with the proposed procedures. The testing should demonstrate that the applicable HMI guidelines are followed, and that the HMI is implemented as specified by the application developer and this OTAC. Refer to Appendix D.3.2 for further information.

Reliability testing should show that the application in its operating environment (OS and hardware included) is stable and deterministic, i.e. identical answers are generated each time the process is entered with identical parameters.

1.2.1 Accuracy testing

Accuracy testing should demonstrate that the aircraft performance or mass & balance computations provided by the application are correct in comparison with data derived from the AFM or other appropriate sources, under a representative cross section of conditions (e.g. for performance applications: runway state and slope, different wind conditions and pressure altitudes, various aircraft configuration including failures with a performance impact, etc.).

The demonstration should include a sufficient number of comparison results from representative calculations throughout the entire operating envelope of the aircraft, considering corner points, routine and break points.

Operators are expected to justify that they covered a sufficient number of testing points with respect to the design of their software application and databases.

Any difference compared to the reference data that is judged significant should be examined and explained. When differences come from a reduced conservatism or reduced margins that were purposely built into the approved data, this approach should be clearly mentioned and motivated. Compliance to the certification and operational rules need to be demonstrated in any case.

The testing method should be described. The testing may be automated when all the required data is available in appropriate electronic format, but in addition to a thorough monitoring of the correct functioning and design of the testing tools and procedures, it is strongly suggested to perform additional manual verification. It could be based on a few scenarios for each chart or table of the reference data, including both operationally representative scenarios and 'corner-case' scenarios.

The testing of a software revision should, in addition, include non-regression testing and testing of any fix or change.

Furthermore, an operator should conduct testing related to its customisation of the applications and to any element proper to its operation that was not covered at an earlier stage (e.g. airport database verification).

1.3 Procedures

In addition to the provisions of paragraph 6.6, specific care is needed regarding the crew procedures concerning performance or mass and balance applications:

- (a) Crew procedures should ensure that calculations are conducted independently by each crew member before data outputs are accepted for use.
- (b) Crew procedures should ensure that a formal cross-check is made before data outputs are accepted for use. Such cross-checks should utilise the independent calculations described above, together with the output of the same data from other sources on the aircraft.
- (c) Crew procedures should ensure that a gross-error check is conducted before data outputs are accepted for use. Such a gross-error check may use either a 'rule of thumb' or the output of the same data from other sources on the aircraft.
- (d) Crew procedures should ensure that, in the event of loss of functionality by an EFB through either the loss of a single application, or the failure of the device hosting the application, an equivalent level of safety can be maintained. Consistency with the EFB Risk Assessment assumptions should be confirmed.

1.4 Training

In addition to the provisions of paragraph 6.13, the training should emphasise the importance of executing all performance calculations in accordance with the SOPs to assure fully independent calculations.

Furthermore, due to the optimisation at different levels brought by performance applications, the crew may be confronted with new procedures and different aircraft behaviour (e.g. use of multiple flaps settings for take-off). The training should be designed and provided accordingly.

Where an application allows computing both dispatch (regulatory calculations, factored calculations) and other results, the training should highlight the specificities of those results. Depending of the representativeness of the calculation, the crew should be trained on the operational margin that might be required.

The training should also address the identification and the review of default values, if any, and assumptions about the aircraft status or environmental conditions made by the application.

1.5 Additional considerations for mass & balance applications

The basic data used for the mass & balance calculation should be modifiable by the EFB Administrator himself/herself or by the software application provider on behalf of the EFB Administrator.

In addition to the figures, a graph should visualise the mass and its associated CG-position.

Appendix G - EFB Policy and Procedures Manual

These are the typical contents of an EFB policy and procedures manual that can be part of the Operation Manual. The proposed outline is very extensive. It may be adapted to the specific EFBs system and to the size and complexity of the operations in which the operator is involved.

EFB Policy & Procedures Manual

Typical Contents

1. Revision history

2. List of effective pages or paragraphs

3. Table of contents

4. Introduction

- Glossary of terms and acronyms
- EFB general philosophy, environment and dataflow
- EFB system architecture
- Limitations of the EFB system
- Hardware description
- Operating system description Detailed presentation of the EFB applications
- EFB application customisation
- Data management:
 - Data administration
 - Organisation & workflows
 - Data loading
 - Data revision mechanisms
 - Approval workflow
 - Data publishing & dispatch
 - Customisation
 - How to manage the airline specific documents
 - Airport data management
 - Aircraft fleet definition
- Data authoring
- Navigation and customisation

5. Hardware and operating system control and configuration

- Purpose and scope
- Description of the following processes:
 - Hardware configuration and part No control

- Operating system configuration and control
- Accessibility control
- Hardware maintenance
- Operating system updating
- Responsibilities and accountabilities
- Records and filing
- Documentary references

6. Software application and configuration

- Purpose and scope
- Description of the following processes:
 - Part No control
 - Software configuration management
 - Application updating process
- Responsibilities and accountabilities
- Records and filing
- Documentary references

7. Flight crew

- Training
- Operating procedures (normal, abnormal, and emergency)

8. Maintenance considerations

9. EFB security policy

- Security solutions and procedures

Appendix H - Airport Moving Map Display (AMMD) Application With Own-Ship Position

1 General considerations

1.1 Preamble

This Appendix guides the applicant in how to demonstrate the safe operational use for AMMD applications as a Type B software application to be hosted in EFBs.

It is recognised that an AMMD can aid pilot positional awareness on the airport manoeuvring area and it is proposed to allow AMMDs to be Type B application under the conditions established in this Appendix H.

1.2 Assumptions of intended use of an AMMD

An AMMD application is **not used as the primary means of taxiing navigation** and is only used in conjunction with other materials and procedures identified within the Operating Concept – see paragraph H.3.

Note: When an AMMD is in use, the primary means of taxiing navigation remains the use of normal procedures and direct visual observation out of the cockpit window.

Thus, as recognised in ETSO-C165a, an AMMD application with display of own-ship position is considered as having a minor safety effect for malfunctions causing the incorrect depiction of aircraft position (own-ship), and the failure condition for the loss of function is classified as 'no safety effect'.

2 Approval of AMMD in EFBs

2.1 Minimum requirements

The AMMD software and database that is compliant with the EASA ETSO-C165a, or an equivalent standard, with following AMMD system features implemented, is considered acceptable:

- (a) The system provides means to display the revision number of the software installed.
- (b) The system is capable of accepting updated airport mapping information and provides means to display the validity period of the database to the flight crew. The flight crew should be able to easily ascertain the validity of the on-board map database. The application should provide an indication when the AMMD database is no longer valid. Refer to section 2.2.5 of RTCA DO-257A as per section 3.1.1 of EASA ETSO-C165a.
- (c) The Total System Accuracy of the end-to-end system is specified and characterised and does not exceed 50 meters (95 %).

Note: An airworthiness-approved sensor using the Global Positioning System (GPS) in combination with a RTCA DO-272 medium accuracy compliant database is considered one acceptable means to satisfy this requirement.

- (d) The system automatically removes the own-ship position when the aircraft is in flight (using e.g. weight on wheels discrete or speed monitoring) and when the estimated position uncertainty exceeds the maximum value. Refer to sections 3 and 4 in Appendix 1 of ETSO-C165a.

- (e) It is recommended that the AMMD detects, annunciates to the flight crew, and fully removes depiction of own-ship data, in case of any loss or degradation of AMMD functions due to failures such as memory corruption, frozen system, latency, etc.

Refer to section 1 in Appendix 1 of EASA ETSO-C165a.

- (f) Data Quality Requirements (DQRs) for the AMMD data base.

2.2 Data provided by the AMMD software application developer

The AMMD software application developer should provide the appropriate data to each integrator in an EFB:

- (a) The executable object code in an acceptable transferring medium;
- (b) Installation instructions or equivalent as per ETSO-C165a section 2.2. addressing:
 - (1) identification of each target EFB system computing platform (including hardware platform and operating system version) with which this AMMD software application and database was demonstrated to be compatible;
 - (2) installation procedures and limitations to address the AMMD installation requirements for each applicable platform such as target computer resource requirements (e.g. memory resources) to ensure the AMMD will work properly when integrated and installed;
 - (3) interface description data including the requirements for external sensors providing data inputs; and
 - (4) verification means required to verify proper integration of the AMMD in the target platform environment, including identification of additional activities that the integrator of an EFB must perform to ensure the AMMD meets its intended function, such as testing in the aircraft.
- (c) Any AMMD limitations, and known installation, operational, functional, or performance issues on the AMMD.

2.3 AMMD software installation in the EFB

The operator should review the documents and the data provided by the AMMD developer and ensure that the installation requirements of the AMMD software in the specific EFB platform and aircraft are addressed. The following activities are required:

- (a) Ensure that the software and database are compatible with the EFB system computing platform on which they are intended to function, including the analysis of compatibility of the AMMD with other EFB Type A and B software applications residing in the same platform. Follow the programme installation instructions provided by the software supplier, as applicable to the compatible EFB computer.
- (b) Check that the objectives for installation, assumptions, limitations and requirements for the AMMD, as part of the data provided by the AMMD software application developer (see H.2.2), are satisfied.
- (c) Perform any verification activities proposed by the AMMD software application developer, as well as identify and perform additional integration activities to be completed.

- (d) Ensure the compatibility and the compliance with requirements for data provided by other installed systems, such as a GNSS sensor and latency assumptions.

3 Operating concept

The operating concept should include, as minimum:

- (a) pilot operation, including confirmation of effectivity;
- (b) handling of updates;
- (c) quality assurance function;
- (d) handling of NOTAMS; and
- (e) the provision of current maps and charts to cover the intended operation of the aeroplane.

Changes to operational or procedural characteristics of the aircraft (e.g. Flight crew procedures) are documented in the Operations Manual or user's guide as appropriate. In particular, the following text is required:

This EFB airport moving map display (AMMD) with own-ship position symbol is designed to assist flight crews in orienting themselves on the airport surface to improve pilot positional awareness during taxi operations. The AMMD function is not to be used as the basis for ground manoeuvring. This application is limited to ground operations only.

4 Training requirements

The operator may use flight crew procedures to mitigate some hazards. This will include limitations on the use of the AMMD function. As the AMMD could be a compelling display and the procedural restrictions are a key component of the mitigation, training should be provided in support of an AMMD's implementation.

Any mitigation to hazards that are mitigated by flight crew procedures should be included in flight crew training. Details of AMMD training should be included in the operator's overall EFB training (refer to Appendix E).

Appendix I - Example of Final Operational Report

System description and classification of EFB system

- A general description of the proposed EFB system
- EFB system (hardware and software applications) proposed (paragraph 4.1)

Software applications

- List of Type A applications installed (paragraph 4.2.1)
- List of Type B applications installed (paragraph 4.2.2)
- List of miscellaneous (non-EFB) software applications installed (paragraph 5.2.2.3)

Hardware (relevant information or references)

For portable EFB used without installed resources:

- EMI compliance demonstration (paragraph 5.2.1.1)
- Lithium battery compliance demonstration (paragraph 5.2.1.2)
- Depressurisation compliance demonstration (paragraph 5.2.1.4)
- Details of the power source (paragraph 5.2.1.3)

For portable EFB served by installed resources:

- Details of the airworthiness approval for the mounting device (paragraph 5.1.1.1.1)
- Description of the placement of the EFB display (paragraph 5.1.1.1.2)
- Details of the use of installed resources (paragraph 5.1.1.1)
- EMI compliance demonstration (paragraph 5.2.1.1)
- Lithium battery compliance demonstration (paragraph 5.2.1.2)
- Depressurisation compliance demonstration (paragraph 5.2.1.4)
- Details of the power source (paragraph 5.1.1.1.3)
- Details of any data connectivity (paragraph 5.1.1.1.4)

For installed EFB:

- Details of the airworthiness approval as installed equipment (paragraph 5.1.1.2)

Certification documentation

- Limitations contained within the AFM (paragraph 5.1.2.1)
- Guidelines for EFB application developers (paragraph 5.1.2.2)
- Guidelines for EFB system suppliers (paragraph 5.1.2.3)

Specific considerations for performance applications

- Details of performance data validation conducted (paragraph 6.5)

Operational assessment

- Details of the EFB risk assessment conducted (paragraph 6.2)
- Details of the human machine interface assessment conducted for Type A and B Software applications (paragraph 6.4)
- Details of flight crew operating procedures (paragraph 6.6):
 - Procedures for using EFB systems with other flight crew compartment systems (paragraph 6.6.1)
 - Flight crew awareness of EFB software/database revisions (paragraph 6.6.2)
 - Procedures to mitigate and/or control workload (paragraph 6.6.3)
 - Flight crew responsibilities for performance calculations (paragraph 6.6.4)
- Details of proposed compliance monitoring oversight of the EFB system (paragraph 6.7)
- Details of EFB system security measures (paragraph 6.8)
- Details of EFB administration procedures including provision of the EFB policy and procedures manual (paragraph 6.10 & paragraph 6.10.1)
- Details of the electronic signatures procedure (paragraph 6.9)
- Details of the system for routine EFB System maintenance (paragraph 6.11)
- Details of flight crew training (paragraph 6.12):
 - Initial training
 - Differences training
 - Recurrent training
- Report of the operational evaluation test (paragraph 6.13):
 - Proposals for the initial retention of paper backup (paragraph 6.13.1)
 - Proposals for the commencement of operations without paper backup (paragraph 6.13.2)
- EFB platform/hardware description;
- Description of each software application to be included in the assessment (see Appendix F);
- Risk assessment summary for each application and mitigation means put in place;
- Human factors assessment for the complete EFB system, human machine interface and all software applications;
 - Pilot workload in both single-pilot and multi-crew flown aircraft
 - Size, resolution, and legibility of symbols and text
 - For navigation chart display: access to desired charts, access to information within a chart, grouping of information, general layout, orientation (e.g., track-up, north-up), depiction of scale information

- Operator training;
- EFB administrator qualification.

Appendix J - Power Supply Considerations for Portable EFBs

If an EFB is permanently attached to the essential power network, it could affect the essential generation system (emergency generator and/or battery, bus bars, distribution system) to which it is connected.

Certification specifications require that an alternate high integrity electrical power supply system, independent of the normal electrical power system, be provided to power those services necessary for continued safe flight and landing, in case of loss of the normal system. Adding other unnecessary services/loads will affect the integrity of this alternate power system. Portable and installed EFBs are considered non-essential equipment and, therefore, not considered necessary for continued safe flight and landing.

It is, therefore, not recommended to connect the EFB to an essential power bus.

Appendix K - Considerations for Rapid Depressurisation Test

When the EFB system hosts applications that are required to be used during flight following a rapid depressurisation, testing is required to determine an EFB device's functional capability. The information from the rapid depressurisation test is used to establish the procedural requirements for the use of that EFB device in a pressurised aircraft. Rapid decompression testing should follow the EUROCAE ED-14G/RTCA DO-160F guidelines for rapid decompression testing up to the maximum operating altitude of the aircraft on which the EFB is to be used. The EFB should be operative for at least 10 minutes after the start of the decompression.

- (a) **Pressurised aircraft:** When a portable EFB has successfully completed rapid depressurisation testing, then no mitigating procedures for the depressurisation event need to be developed. When a portable EFB has failed the rapid depressurisation testing while turned ON, but successfully completed it when OFF, then procedures will need to ensure that at least one EFB on board the aircraft remains OFF during the applicable flight phases or configured so that no damage will be incurred should rapid decompression occur in flight above 10 000 ft AMSL.

If the EFB system has not been tested or has failed the rapid depressurisation test, then alternate procedures or paper backup should be available.

- (b) **Non-Pressurised aircraft:** Rapid decompression testing is not required for an EFB used in a non-pressurised aircraft. The EFB should be demonstrated to reliably operate up to the maximum operating altitude of the aircraft. If EFB operation at maximum operating altitude is not attainable, procedures should be established to preclude operation of the EFB above the maximum demonstrated EFB operation altitude while still maintaining availability of the required aeronautical information.

Appendix L - Example of Operations Specifications and Operations Manual Content

When an EFB function is to be used for the safe operation of an aeroplane, an entry must be included in the operator’s operations specifications approved by the OTAA.

The operations specifications will reference the location in the operations manual where the approved EFB applications are detailed. Figure L-1 shows an example of a specific approval EFB entry.

OPERATIONS SPECIFICATIONS (Subject to the approved conditions in the operations manual)				
SPECIFIC APPROVAL	YES	NO	DESCRIPTION	REMARKS
Continuing airworthiness	X	X		
EFB for A/C type <i>Type 1</i>			18 - Specifically approved EFB hardware and software applications for A/C type <i>Type 1</i> are contained in [operations manual reference]	
Other				

Note: List the EFB functions with any applicable limitations.

Figure L-1. Example of a specific approval EFB entry

Note: Boxes YES/NO are not used since some EFB functions might not require an operational approval. Other EFB functions not requiring an EFB approval should not be listed in the operations specifications form.

The EFB-specific approvals referenced in the operations specifications form should have a companion detailed list of EFB-approved hardware and software applications. This list should be located in the operations manual in a table and be updated through the normal operations-manual-approval process established by the State. Figure L-2 contains an example of a companion EFB-specific approval table.

The “Approved hardware for A/C type” column of the companion *EFB (hardware and software) with specific approval table* should match the “DESCRIPTION” column of the operations specifications form. The “EFB applications” column of the table should list all the applications requiring a specific approval and include the application version, with any applicable limitations. The “Specific references and/or remarks” column of the table should include the application version in addition to any specific operations manual reference and other remarks, if applicable.

EFB (hardware and software) with specific approval		
Approved hardware for A/C type	EFB applications <i>(List of EFB functions, versions and any applicable limitations.)</i>	Specific references and/or remarks
EFB for A/C type <i>Type 1</i>	– Aircraft performance calculation (take-off and landing) – <i>AppName1 ver x.x</i>	<i>See procedures in operations manual page X Backup: Quick Reference Handbook</i>
	– Airport moving map – <i>AppName2 ver x.x</i>	<i>Refer to operations manual page X</i>
	– Charts application: En route – <i>AppName3 ver x.x</i>	<i>See operations manual page Y. Paper backup operation</i>
	– Airport charts (SID, STAR, approach) – <i>AppName4 ver x.x</i>	<i>Paperless operation Refer to operations manual page Z</i>
EFB for A/C type <i>Type 2</i>	– Charts application: En route – <i>AppName3 ver x.x</i>	<i>See operations manual page X Paper backup operation</i>

Figure L-2. Example of a companion EFB-specific approval table